

2009 JAMIS KOMODO II

UPGRADES FROM 2008

New frame design with shorter chainstays, lower stand-over and more aggressive DJ/urban geo

Maxxis Larsen TT tires

New FSA StepUp crank

Shimano SLX Shadow rear derailleur

Shimano RapidFire Plus shifter

REASONS TO UPGRADE FROM KOMODO I

Marzocchi Dirt Jumper Fork

Hayes Stroker Ryde hydraulic brakes

New Shimano SLX rear derailleur

185mm front rotor



Champagne

FEATURES/BENEFITS

Go dirt jumping, take it on an urban assault mission, hop around the rocks, take it to the trail or ride it to school: this bike is the perfect tool.

This frame lives up to the Komodo name: stout Kinesis-manufactured 7005 tubing, double-gusseted, with massive 57mm down tube ovalized to 72mm at the head tube for impressive frontal strength

A 35mm seat tube with 31.6mm seat post assures the stiffest possible pedaling & steering platform, with a sloping rifled top tube for low stand-over

The '09 Komodo's rear wheel has been tucked super tight against the seat tube with short 410mm chainstays. With our new dropouts, you've got a stiffer more responsive rear end. Nothing personal, of course

"Marzocchi Dirt Jumper 1" fork says it all: 32mm aluminum stanchions, 100mm of travel with a 20mm thru axle, and suspension that carries the Marzocchi name

Shimano's new SLX Shadow derailleur features a QUIET super low-profile design that won't slap the chainstay in rough riding conditions. Direct cable routing reduces the risk of housing snag.

The Shadow derailleur features a stronger return spring that delivers positive, crisp shifts. It was clearly designed specifically for the rigors of aggressive trail riding

FSA's new FSA StepUp crank with ISIS splined BB, 32/22T heat-treated rings and 170mm crank arms with chromoly pedal inserts delivers the pedaling platform confidence DJ riders demand

Hayes Stroker Ryde hydraulic disc brakes were designed with insulated caliper pistons to control fluid temperature eliminating lever fluctuation & provide a reliable feel every ride, all conditions

The large brake pads yield optimal heat management and, in tandem with the V7 185mm rotor up front and V6 rotor in back, deliver lots of power.

WTB's Speed V Sport SE Saddle features a soft elastomer shell with a deep padding set to provide maximum comfort

The Komodo's Maxxis Larsen TT tires offer SUPER low-rolling resistance with enough tackiness to hold a line in the sharpest of corners

SPECIFICATIONS

Frame	7005 triple gauge aluminum main tubes, 1.5" head tube, gusseted main frame, heavy-duty stays, rifled top tube, replaceable derailleur hanger
Fork	Marzocchi Dirt Jumper 1, 32mm aluminum stanchions, 20mm thru axle, rebound damping adjustor, air preload, 100mm travel
Headset	Zero-Stack internal cup, threadless, 20mm shim stack, with 1.5" to 1-1/8" reducer
Wheels	Weinmann Taurus 2000 eyeletted rims, Formula DH-DC91 20mm thru-axle front & Formula DC30 rear disc hubs, 14g black stainless steel spokes
Tires	Maxxis Larsen, 26 x 2.35"
Derailleurs	Shimano SLX Shadow rear, SR XC-202 34.9mm dual pull front
Shiftlevers	Shimano Alivio Rapidfire SL, 16-speed
Chain	KMC Z82
Cassette	Shimano HG40, 8-speed, 11-32
Crankset	FSA Step-Up, 32/22, with polycarbonate bash guard, 170mm (all frame sizes)
BB Set	FSA ISIS, sealed cartridge, 73 x 113
Pedals	Flatbed alloy platform type with pedal spikes
Brakeset	Hayes Stroker Ryde hydraulic disc brakes, V7 front and V6 rear rotors
Handlebar	Jamis DJ 6061 T-6 riser bar, 31.8 O° x 86mm rise x 640mm
Stem	Jamis DJ alloy 4-bolt bar clamp threadless, 31.8 bar bore x 30° rise x 50mm
Grips	WTB Weirwolf, dual DNA compound
Seat Post	Jamis OS alloy micro-adjust, 31.6 x 350mm with alloy QR clamp
Saddle	WTB Speed V Sport SE with SL cover
Sizes	14", 16.5", 18.5"
Color	Champagne
Weight	32.50 lbs

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
S/14"	12.52/318	22.48/571	68.5°	71.5°	16.14/410	41.81/1062	1.50/38	13.46/342	5.12/130	27.16/690
M/16"	14.09/358	23.50/597	68.5°	71.5°	16.14/410	42.79/1087	1.50/38	13.46/342	5.12/130	27.99/711
L/18"	15.98/406	24.41/620	68.5°	71.5°	16.14/410	43.70/1110	1.50/38	13.46/342	5.51/140	28.97/736