

# 2010 XENITH T

NEW MODEL FOR 2010

## REASONS TO UPGRADE FROM XENITH TEAM

Xenith T series full carbon aero frame

Shimano's new 6700 Ultegra components

Alex ALX-320 wheelset

FSA Gossamer BB30 crank

Profile T2 Wing base bar and Aris stem



Pearl White/Carbon

## FEATURES/BENEFITS

Xenith T features high modulus carbon construction using NACA guidelines for aero profiles, San Diego Low-Speed Wind Tunnel tested, with the rear brake tucked under the chain stay for a cleaner air flow; internal cables for smooth, clean aero lines; a redesigned seat tube to shield the rear wheel from the wind; and an aero- clean seat post/seat tube juncture with aero seat stays.

Xenith T series frames move to the BB30 system in '10 for lighter and smoother spinning cranks. It's more aerodynamic too, than outboard bearing systems since the bearings are inside the BB shell.

Our patent pending, full carbon monocoque WindShield fork encloses the front brake within the fork blades for superior aerodynamics, with easy-access brake ports to simplify brake maintenance.

The Xenith T series carbon seatpost features an aero profile and micro-adjustability for fine tuning the seat angle.

Alex ALX-320 wheelset is light enough to be used on race day and durable enough to provide lots of carefree training miles.

FSA Gossamer BB30 crank is light weight and features full size 53/39 chainrings for top end speed to help you set your personal best split.

Tektro's TT-specific brakeset offers a more compact shape for improved aerodynamics, with Kool Stop pads for superior braking performance.

Tektro's aero brake levers feature increased leverage to optimize braking performance.

Shimano's new 6700 Ultegra drivetrain is paired with Dura Ace bar end shifter for smooth dependable shifting.

Profile Design's aero cockpit offers complete adjustability and comfort in a surprisingly lightweight package.

Vittoria's Zaffiro slick 23c tires offer legendary, road-holding capability and superior ride quality.

Selle San Marco's Trilon saddle is specifically designed for Tri/TT bikes with a padded nose, chromoly rails and classic Italian styling.

A full range of sizes is available, including an XS size with 650c wheels.

## SPECIFICATIONS

Frame	Hi-modulus carbon composite Tri/TT frame, NACA compliant profiles, chainstay-mounted rear brake, internal cable routing, seat tube has full rear wheel recess, flat-oval top tube, aerofoil seatstays, rear-entry horizontal dropouts with axle-position adjustment bolts
Fork	Windshield aero full carbon with rear-facing/enclosed front brake for reduced aerodynamic drag, with brake pad adjustment ports
Headset	FSA Internal AheadSet, 11/8"
Wheels	Alex A-Class ALX-320, 24/20H, radial front/2X rear, sealed bearing hubs, DT Stainless black spokes
Tires	Vittoria Zaffiro Slick, 700x23c (Vittoria Rubino 650x23c for XS)
Derailleurs	Shimano Ultegra RD- 6700 rear and 105 FD-5600 braze-on front
Shiftlevers	Shimano Dura Ace, SL-BS79, 10-speed bar end shifters
Chain	KMC DX10SC
Cassette	Shimano CS-5600, 10-speed, 11-25T
Crankset	FSA Gossamer for BB30, 53/38T, 170mm (XS, S), 172.5mm (M), 175mm (L, XL)
BB Set	FSA BB30
Pedals	NA
Brakeset	Tektro R725 aero TT brake with Kool Stop dual-compound cartridge shoes, Tektro TL-720 brake levers
Handlebar	Profile T2+ extensions, T2 Wing base bar, 400mm (XS, S, M), 420mm (L, XL)
Stem	Profile Aris 3D forged, 7D x 90mm (XS, S, M), 100mm (L, XL)
Grips	Jamis suede bar tape
Seat Post	Jamis Aero carbon post
Saddle	Selle San Marco Ponzia TT with Hollow Cro-moly rails
Sizes	XS (650c), S, M, L, XL
Color	Pearl White/Carbon

## GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	STACK	REACH	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
XS 47 (650c)	18.19/462	19.09/485	72°	78°	18.15/461	15.24/387	14.37/365	36.5/927	1.69/43	10.11/257	3.94/100	27.64/718
S	19.88/505	20.08/510	71°	78°	19.53/496	15.95/405	15.35/390	38.8/986	1.89/48	10.63/270	3.94/100	29.80/757
M	20.27/515	20.67/525	72°	78°	20.04/509	16.42/417	15.35/390	39.1/994	1.89/48	10.63/270	4.33/110	30.31/770
M/L	21.02/534	21.45/545	72°	78°	20.91/531	17.01/432	15.35/390	40.0/1074	1.89/48	10.63/270	5.31/135	31.26/794
L	22.24/565	22.64/575	72°	78°	21.89/556	17.99/457	15.35/390	41.3/1049	1.89/48	10.63/270	6.30/160	32.20/818