

2016 HALO XCT



Dark Shadow

SPECIFICATIONS

Frame	Triple-buttet 6061 alloy, 130mm travel mp4 suspension, asymmetrical chainstays with 12 x 142mm dropouts, 1 1/8" - 1.5" tapered head tube, dropper post routing, ISCG05 chainguide mounts, Enduro® Max sealed bearing pivots, X-Fusion O2 Pro RL high volume shock, 10mm hardware, replaceable derailleur hanger, Formula axle
Fork	X-Fusion Streat RL2 27.5" with 15mm axle, 32mm stanchions, tapered alloy steerer, air spring compression, rebound & lockout adjust, magnesium lower legs, 130mm travel
Headset	FSA Orbit 1.5 Zero-Stack internal cup for tapered head tube, 8mm cone spacer
Wheels	WTB ST i23 TCS 27.5" tubeless rims, 32H, Formula sealed bearing 15mm front and 12 x 142mm rear 6-bolt disc hubs, stainless spokes
Tires	Vittoria Goma, 27.5" x 2.25", folding
Derailleurs	Shimano Deore Shadow Plus rear and Deore front
Shiftlevers	Shimano Deore, 2x10-speed
Chain	Shimano HG54, 10-speed
Cassette	Shimano HG50, 10-speed, 11-36T
Crankset	Shimano Deore M617, 36/22T, 170mm (14"/16"), 175mm (18")
BB Set	Enduro® BSA
Pedals	N/A
Brakeset	Shimano M396 hydraulic disc, 180mm front & 160mm rear RT56 rotors
Handlebar	Ritchey Trail, 690mm x 20mm rise, 9° sweep
Stem	Ritchey Trail, 60mm (14"), 70mm (16"), 80mm (18")
Grips	Jamis Lock-On
Seat Post	KS eTen, 100mm travel, handlebar remote, 385mm x 31.6
Saddle	WTB Volt Comp with Luxe Zone Cut-Out
Sizes	14", 16", 18"
Color	Dark Shadow

CHANGES/UPGRADES FROM 2015

- Enduro® Max sealed bearing pivots
- X-Fusion Streat RL2 & O2 Pro RL suspension
- Shimano Deore Shadow Plus RD
- WTB ST i23 TCS tubeless rims
- Shimano M396 brakeset
- Enduro® premium bottom bracket
- WTB Volt Comp with Luxe Zone Cut-Out saddle

TOP 5 THINGS YOU NEED TO KNOW

USA made Enduro® Max sealed bearings sustain 40% more load capacity than standard radial bearings & provide more lateral support for the multiple forces associated with mountain bike pivots.

X-Fusion has obsessively focused on producing the highest performance, highest quality and highest value suspension products for mountain bikes since 1999. They pride themselves on building XF products entirely of metal parts because they know it's what's on the inside that makes a difference.

Shimano's Deore 36/22T crankset and 11-36T cassette supplies a 2x10 set-up with a wide range of gear ratios to take on any terrain.

Shimano's Deore Shadow Plus rear derailleur features an on/off chain stabilizer system that reduces chain slap and is lighter and more efficient than a roller type chain device.

Enduro®'s external BSA bottom bracket is produced in the USA using Grade 10 Chromium balls that are twice as round as the industry standard. Hardened & polished High Carbon Chromium races yield extremely tough, durable and noiseless ABEC-3 precision.

GEOMETRY

SIZE	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
14	21.2 / 540	69°	74°	17.7 / 450	42.9 / 1090	0.5 / 13	3.9 / 100	29.0 / 737	22.7 / 576	14.9 / 378
16	22.1 / 560	69°	74°	17.7 / 450	43.5 / 1106	0.5 / 13	4.3 / 110	29.7 / 755	23.0 / 585	15.4 / 390
18	22.9 / 580	69°	74°	17.7 / 450	44.4 / 1127	0.5 / 13	4.7 / 120	30.7 / 779	23.4 / 595	16.0 / 407