

REYNOLDS

SST

ECO

2016 RENEGADE EXPAT



Gloss Black

ROAD - Adventure

SPECIFICATIONS

Frame	Jamis Adventure frame, Reynolds 520 double-buttet SST chromoly main tubes, butted and tapered seat tube for 27.2 seat post, 44mm head tube for tapered fork, threaded BB shell, seat stay disc brake mounts, top tube mounted full cable housing, accepts 3 waterbottles, rack and fender mount eyelets, with clearance for 40c tires.
Fork	Jamis Adventure ECO monocoque carbon composite fork, 15mm thru-axle dropout with stainless interface, tapered steerer with 1.5" hollow formed crown, post disc brake mounts with integrated cable cradle with carbon dropouts, hidden fender mount eyelets and stainless axle interfaces
Headset	FSA Orbit ITA B Internal/External, 1 1/8" - 1.5"
Wheels	Alex ATD 470 disc rim with TCS (Tubeless Compatible System), 32H, Formula alloy disc road hubs and 14g stainless steel spokes
Tires	Clement X Plor USH, 700 x 35c, 30tpi with protection belt
Derailleurs	Shimano Tiagra RD-4700 GS rear and Tiagra FD-4700 front with 28.6mm alloy clamp
Shiftlevers	Shimano Tiagra ST-4700 Dual Control STI, 20-Speed
Chain	KMC 10-speed X10
Cassette	Shimano 10-Speed 12-30T
Crankset	FSA Omega MegaExo compact double, 50/34T, 170mm (48/51) 172.5mm (54/56) 175mm (58/61)
BB Set	FSA BB-4000
Pedals	N/A
Brakeset	TRP Spyre mechanical cable actuated disc brake with 160mm rotors and Shimano Tiagra ST-4700 brake levers
Handlebar	Ritchey Evomax Comp, 6061 aluminum, 73 reach, 120 drop with 12° flare, 31.8 x 420 (48-51) 440mm (54-56), 460mm (56-61)
Stem	Ritchey 4-Axis 3D forged 6061 alloy, 6" x 80mm (48/51), 90mm (54/56), 110mm (58/61)
Grips	Jamis suede tape with Jamis logo and "J" end plug
Seat Post	Ritchey Road, 27.2 x 300mm with chromo seat pin
Saddle	Selle Royal Seta S1 with fine grain cover, steel rails with integrated clip system
Sizes	48, 51, 54, 56, 58, 61cm
Color	Gloss Black

UPGRADES/CHANGES FROM 2015

New Adventure model for 2016!!

REASONS TO UPGRADE FROM RENEGADE EXILE

Jamis Adventure Reynolds 520 double-buttet SST chromoly frame

New Tiagra 4700 group

FSA Omega MegaExo 50/34T

TRP Spyre mechanical cable actuated disc brake

Ritchey 4-Axis Stem and seat post

TOP 5 THINGS YOU NEED TO KNOW

Shimano's new Tiagra 4700 10-Speed group incorporates many of the trickle down benefits of its big brothers. Reduced shifting effort, better braking from the hoods, more control based on better ergonomics and durability which is a must when taking your adventure off road.

TRP's Spyre is a dual-sided mechanical where both pads actuate providing more even and precise clamping force. This translates into even and consistent pad wear. With the addition of a simple cable barrel adjuster, the pads can be adjusted easily and hassle free.

The Alex ATD470 rim with TCS (Tubeless Compatible System) features a tubeless ready rim with a reinforced rim bed to counter-act disc brake forces. This wheelset is ready for your next adventure.

Tom Ritchey has done it again with the EVOMAX bar. This time TR has taken his shallow drop (120mm) and short reach (73mm) bar and added a 12° flare at the drop for a wider bar that increases stability, and clearance between your forearm and the top bar while hitting the roughest terrain.

Clement has not only taken CX by storm, they are now focused on the Adventure market. The X'Plor USH is a 700 x 35 mm adventure tire USH is designed for mixed conditions. The combination of firm center ridge and diamond-shaped side knobs provide low rolling resistance and great cornering control.

GEOMETRY

SIZE	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
48	20.43 / 519	70.5°	73°	16.81 / 427	39.25 / 997	2.24 / 57	2.89 / 73.5	3.27 / 83	28.50 / 724	20.27 / 515	14.17 / 360
51	21.02 / 534	71°	73°	16.81 / 427	39.57 / 1005	2.09 / 53	2.89 / 73.5	3.94 / 100	29.33 / 745	21.06 / 535	14.53 / 369
54	21.69 / 551	71.5°	73°	16.93 / 430	40.27 / 1023	2.09 / 53	2.83 / 72	5.20 / 132	30.55 / 776	22.24 / 565	14.88 / 378
56	22.44 / 570	71.5°	73°	16.93 / 430	41.02 / 1042	2.09 / 53	2.83 / 72	6.42 / 163	31.53 / 801	23.43 / 595	15.24 / 387
58	23.07 / 586	72°	73°	16.93 / 430	41.38 / 1051	1.97 / 50	2.77 / 70.5	7.40 / 188	32.48 / 825	24.41 / 620	15.59 / 396
61	23.66 / 601	72.5°	73°	17.2 / 435	41.97 / 1066	1.97 / 50	2.77 / 70.5	8.15 / 207	33.31 / 846	25.20 / 640	15.94 / 405