

# DAKOTA TEAM

## SPECIFICATIONS

Frame	High Modulus Dyad Supreme carbon fiber, 1.5 - 1 1/8" tapered head tube, PressFit30 BB shell, High Direct Mount (HDM) front derailleur with internal cable routing, post mount disc brakes & 12x142 drop-outs, stainless steel chain stay protector, replaceable derailleur hanger, Rock Shox Maxle axle
Fork	Fox 32 Float Step Cast Factory Series 29" w/2-position remote & Open Mode Adjust, Kashima Coating, 15x110mm axle, air spring compression, rebound adjust, tapered alloy steerer, 100mm travel
Headset	FSA Orbit 1.5 Zero-Stack internal bearing, 8mm cone spacer
Wheels	Stan's NoTubes Crest MK3 Team 29" tubeless wheels, Neo Series 32H 15x110mm axle front and 12x142mm rear hubs, Sapim Custom Force spokes
Tires	Vittoria Peyote, 29 x 2.1", TNT tubeless
Derailleurs	SRAM XX1 Eagle, 12-speed
Shiftlevers	SRAM XX1 Eagle, 1x12-speed
Chain	SRAM XX1 Eagle, 12-speed
Cassette	SRAM XG-1295, 12-speed, 10-50T
Crankset	SRAM XX1 Eagle, 34T, 170mm (15"), 175mm (17"-21")
BB Set	Enduro® PressFit 30
Pedals	N/A
Brakeset	Shimano XTR M9020 Ice-Tech hydraulic disc, 180mm front & 160mm rear RT-86 Ice-Tech rotors
Handlebar	Ritchey Trail WCS Carbon 2x, 31.8 x 9" sweep x +/- 5mm rise x 710mm
Stem	Ritchey Trail WCS, 70mm (15"), 80mm (17"), 90mm (19"), 100mm (21")
Grips	Jamis Lock-On
Seat Post	Ritchey Trail WCS Carbon, 31.6 x 400mm
Saddle	WTB Volt Comp
Sizes	15", 17", 19", 21"
Color	Charcoal
Weight	20.0 lbs



Available as frameset

## TECH FEATURES



## UPGRADES/CHANGES FROM 2016

- Fox 32 Step Cast Factory Series fork
- SRAM XX1 Eagle 1x12 drivetrain
- Shimano XTR Ice-Tech brakes
- Stan's Crest MK3 wheelset
- Ritchey Trail cockpit

## REASONS TO UPGRADE FROM DAKOTA PRO

- High-modulus Dyad Supreme carbon
- Fox Factory Series fork
- Stan's Crest MK3 wheelset
- SRAM XX1 Eagle 1x12 drivetrain
- Shimano XTR Ice-Tech brakes

## GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
15	22.6 / 575	70.5°	73°	17.2 / 438	42.0 / 1066	22.8 / 58	3.9 / 100	29.6 / 752	23.9 / 608	15.3 / 389
17	23.6 / 600	70.5°	73°	17.2 / 438	42.8 / 1088	22.8 / 58	4.3 / 110	29.7 / 755	24.3 / 618	16.1 / 410
19	24.4 / 620	70.5°	73°	17.2 / 438	43.8 / 1112	22.8 / 58	4.53 / 115	30.4 / 773	24.5 / 623	16.9 / 430
21	25.2 / 640	70.5°	73°	17.2 / 438	44.6 / 1132	22.8 / 58	5.1 / 130	32.2 / 817	25.1 / 638	17.5 / 445