



Candy Apple

UPGRADES/CHANGES FROM 2009 (DURANGO 29)

- Lower price point!
- New Shimano Deore Shadow rear & FD-M311 front derailleurs
- Shimano FC-M361 crankset
- WTB black stainless steel 14g spokes
- Tektro IO cable actuated brakes
- Jamis Trail saddle

REASONS TO RIDE A 29'ER

- Larger diameter wheels roll over obstacles more easily due to decrease in approach angle
- Larger wheels have a lower rolling resistance for the same tire width
- Larger wheels are less prone to sinking in mud or sand
- Larger contact patch increases cornering traction
- Larger wheels are less prone to pinch flattening
- The 29'er geo offers taller riders a more natural frame geometry

FEATURES/BENEFITS

Same frame as the higher-end Exile II, so you get the same great handling characteristics with a semi-integrated head tube & formed down tube for increased frontal strength, and S-shaped top tube for low standover.

Rock Shox's Dart 29er fork offers magnesium lowers for light weight, 30mm stanchions for a stiff, solid ride and TurnKey lockout for a climbing advantage.

Shimano's new Deore Shadow derailleur features a quiet super low-profile design that won't slap the chainstay in rough riding conditions. Direct cable routing reduces the risk of housing snag.

The Shadow derailleur features a stronger return spring that delivers positive, crisp shifts. It was clearly designed specifically for the rigors of aggressive trail riding.

Shimano's M361 crankset features Hyperdrive SG-X chainrings for exceptionally precise & quick shifting performance.

Shimano's HG40 8-speed cassette offers the same precise shifting attributes of the higher priced 9-speed cog sets, with patented tooth profiles and shifting ramps.

Tektro's IO disc brakes offer great braking control in all conditions and actually help increase rim life by not using the rim sidewall as a braking surface.

Disc brake torque twists the hub during braking, exerting "pull" load on the spokes and nipples. We specify eyeletted WTB rims because the eyelets help to strengthen the rim bed and prevent spoke/nipple shear due to disc brake torque.

The Exile I's cockpit includes 31.8 over-sized bars and stem for stiffer, more solid handling.

WTB's Speed V Sport saddle offers an extra wide platform to support riders of all shapes, with extra long rails to promote a better fit.

SPECIFICATIONS

Frame	Kinesis 6061 T6 aluminum with crown-clearing goose-necked down tube, low-standover curved top tube, replaceable derailleur hanger
Fork	Rock Shox Dart 3 29'black er, magnesium sliders, external preload and rebound damping, TurnKey lockout, 28mm stanchions, 100mm travel
Headset	FSA ZS-4 semi-integrated with 20mm shim stack, 11 / 8"
Wheels	WTB Speed Disc eyeletted rims, 32H, Formula alloy disc hubs, WTB 14g black stainless steel spokes
Tires	Maxxis Ignitor, 29 x 2.1"
Derailleurs	Shimano Deore rear and Acera, 34.9mm top pull front
Shiftlevers	Shimano Acera RapidFire-SL, 24-speed
Chain	KMC Z9000
Cassette	Shimano HG40, 8-speed, 11-32
Crankset	Shimano Deore M361 44/32/22, 170mm (12-15.5"), 175mm (17-21")
BB Set	Shimano UN26, 68 x 121
Pedals	Alloy platform with steel outer cage
Brakeset	Tektro IO mechanical disc brakes, ML-330 levers and 160mm wavy rotors
Handlebar	Jamis XC alloy riser, 6D sweep x 13mm rise x 620mm wide
Stem	Jamis XC alloy threadless, 10D rise x 75mm (12-14"W), 90mm (14M-15.5"), 100mm (17"), and 120mm (19-21")
Grips	Velo Kraton, medium diameter
Seat Post	Jamis alloy micro-adjust, 31.6 x 350mm, with alloy QR clamp
Saddle	Jamis Trail with pressure relief channel, wide tail platform and scuff-resistant corners
Sizes	15", 17", 19", 21"
Color	Candy Apple

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
15"	13.42/341	22.44/570	72°	74°	17.72/450	42.16/1071	1.81/46	12.79/325	3.74/95	28.97/736
17"	14.53/369	23.23/590	72°	73.5°	17.72/450	42.75/1086	1.81/46	12.79/325	3.74/95	29.49/749
19"	15.98/406	24.02/610	72°	73°	17.72/450	43.31/1100	1.81/46	12.79/325	3.94/100	30.31/770
21"	17.28/439	24.61/625	72°	73°	17.72/450	43.90/1115	1.81/46	12.79/325	3.94/100	30.98/787