CITIZEN

SPECIFICATIONS

Frame	Hi-tensile steel frame, sloping design for men's, step through design for ladies, center-mount kickstand plate and fender/rack eyelets
Fork	Hi-tensile steel unicrown, radius blades with dropout eyelets
Headset	Water-resistant sealed mechanism, threaded, 1 1/8"
Wheels	Alloy rims, 36H, alloy hubs with QR and 14g stainless steel spokes
Tires	CST Marathon/Tour C-1446 with silver safety stripe, 700 x 38c
Derailleurs	Shimano Tourney RD-TY500 rear
Shiftlevers	Shimano Revoshift, SL-RS35, 7-speed
Chain	KMC Z7
Cassette	Shimano MF-TZ31 7-speed, 14-34T
Crankset	Forged alloy crank, single 44T, 170mm with chainguard
BB Set	FSA sealed cartridge, 68 x 122.5mm
Pedals	Comfort platform style
Brakeset	Promax TX-121 linear-pull with Tektro CL530 ergonomic design alloy levers with kraton insert
Handlebar	Comfort hi-rise, steel, 25.4 x 80mm rise x 15˚ sweep x 640mm
Stem	Jamis alloy hi-rise, 35˚ rise x 90mm with 150mm quill (14–18"), 110mm with 180mm quill (19–23")
Grips	Anatomic triple density kraton grip
Seat Post	Jamis alloy micro-adjust, 25.4 x 350mm with alloy QR clamp. 300mm for Men's 15, 17, Step-Thru 14
Saddle	Jamis Comfort with synthetic suede cover, burnished sides and bumper springs with satin steel rails, gender specific
Accessories	Kickstand
Sizes	M: 15", 17", 19", 21", 23" S/T: 14", 18"
Color	M: Gloss Black or Winter Blue S/T: Winter Blue or Lavender Pearl
Weight	30.75 lbs

Gloss Black

UPGRADES/CHANGES FROM PREVIOUS MODEL

New Model

Winter Blue

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER
15	21.53 / 547	70°	74 °	17.52 / 445	41.69 / 1059	1.97 / 50	2.56 / 65	4.72 / 120	28.27 / 718
17	22.11 / 562	70°	74 °	17.52 / 445	42.28 / 1074	1.97 / 50	2.56 / 65	4.72 / 120	29.33 / 745
19	22.48 / 571	71°	73.5 °	17.52 / 445	42.05 / 1068	1.97 / 50	2.56 / 65	4.72 / 120	30.59 / 777
21	23.06 / 586	71°	73.5 °	17.52 / 445	42.68 / 1084	1.97 / 50	2.56 / 65	5.12 / 130	32.05 / 814
23	23.46 / 596	71°	73.5 °	17.52 / 445	43.07 / 1094	1.97 / 50	2.56 / 65	5.71 / 145	32.95 / 837
14 S/T	21.49 / 546	70°	74°	17.52 / 445	41.73 / 1060	1.97 / 50	2.56 / 65	5.90 / 150	18.98 / 482
18 S/T	21.85 / 555	70°	73.5°	17.52 / 445	41.89 / 1064	1.97 / 50	2.56 / 65	6.49 / 165	18.54 / 471