

All Jamis suspension frame parts are sold as the complete Parts Kit Assemblies listed below.

Individual parts are not sold separately.

Bell Crank Pivot Assembly, Part # 12-2604

| Item # | Description | Quantity | Torque |
|--------|--------------------------------|----------|--------|
| 04 | Bearing – 24x08xT8, 628-ZZ | 4 | |
| 05 | Nut – 08x27L,M8x1.125, 6061-T6 | 1 | |
| 06 | Bolt – 23.5x36.5L, 7075 | 2 | 60KGF |
| 07 | Bolt – 23.5x26.5L, 7075 | 2 | 60KGF |
| 17 | Spacer – 8.1x12x18xT6.0, 6061 | 2 | |

Drop Out Pivot Assembly, Part #12-2602

| Item # | Description | Quantity | Torque |
|--------|----------------------|----------|--------|
| 14 | Axle – M6x1.0/08xL15 | 2 Sets | 60KGF |
| 16 | Bearing – 19x08xW6 | 2 | |

Bottom Bracket Pivot Assembly, Part # 12-4050

| Item # | Description | Quantity | Torque |
|--------|---|----------|--------|
| 08 | Bolt – 29.5x17x2.5x25L, 7075-T6 | 2 | 130KGF |
| 09 | Bearing – 30x17xW7, #6903-2RS | 2 | |
| 10 | Spacer – 24x17xt3.5, Stainless | 2 | |
| 11 | No head Screw – M12x1.75xL52, Stainless | 2 | |

Bell Crank, Part # 12-2612

| Item # | Description | Quantity | Torque |
|--------|-----------------------|----------|--------|
| 19 | Bridge – 7005 | 1 | |
| 20 | Bolts – M6x1.0xL12 | 4 | |
| 03 | Bell Crank Arms, 7005 | 2 | |

Shock Mounting Bolts, Part # 12-2308

| Item # | Description | Quantity | Torque |
|--------|----------------------|----------|--------|
| 15 | Axle – 10xM6x1.0xL45 | 1 | 80KGF |
| 01 | Axle – 10xM6x1.0xL34 | 1 | 80KGF |
| 02 | Bolt – M6x1.0xL17 | 2 | |

Derailleur Hanger, Part # 12-6675

| Item # | Description | Quantity | Torque |
|--------|---------------|----------|--------|
| 12 | Mounting Bolt | 1 Set | |
| 13 | Alloy Hanger | 1 | |

Shock Specifications

| |
|-------------------------------------|
| Eye to Eye – 165mm |
| Stroke – 57mm |
| Mounting Hardware Front – 10x22.4mm |
| Mounting Hardware Rear – 10x33.4mm |
| Sag Suggestion 14-19mm |

Frame Specifications

| |
|--|
| Heat tube: 44mm I.D. Zero Stack, Internal Cup type, 1-1/8" |
| BB Shell – 73mm |
| Rear axle Spacing – 135mm |
| Seat Tube I.D. - 31.6mm |
| Seat Tube O.D. - 34.9mm |

