

2009 JAMIS CITIZEN 1

UPGRADES FROM 2008

Impossible to improve!

"Great bike for comfort riding. I found it to be the most comfortable bike I test rode at several bike shops." -- Consumer review on Buzzillions.com



Forest Green



Gloss Black



Violet Mist

FEATURES/BENEFITS

Large diameter 700c road bike wheels roll faster & more predictably at speed and roll over bumps & potholes more comfortably than smaller diameter 26" wheels

Lightweight & durable aluminum frame with formed down tube & bullet style cable guides for good looks and increased strength

Sloping double diamond frame design in 7 sizes assures best possible customer fit for more comfort, better handling, increased safety

The Citizen 1's suspension fork offers 2 1/2" (63mm) of coil sprung suspension, a lightweight alloy crown, and mini-boots to protect sliders

Our smooth-rolling, inverted tread 700 x 38c tires hold more air volume & are more comfortable to ride than smaller width 23 - 28C road tires.

These tires feature a reflective sidewall stripe which, in tandem with the CPSC rated wheel reflectors, enhance visibility in the dark. But don't forget your lights!

21-speed twist shifting drivetrain features a full size 48/38/28 crankset with chainguard, Shimano Altus rear derailleur and Mega-Range freewheel for easy climbing

A near all alloy parts list -- alloy micro-adjust seat post, alloy stem, alloy crank, alloy seat post clamp, alloy hubs, alloy rims alloy brakes & levers, alloy kickstand -- reduces weight, adds value, and is rust-proof

Super plush comfort saddle with slip resistant suede-type top, "thigh glide" burnished sides, elastomer springs -- with Male & Female specific saddle lengths & widths

Telescoping suspension seat post with 1" of coil-sprung travel smooths out the road and trail

Long quilled, angle-adjustable stem and 3" rise handlebars offer a comfortable, upright ride position that's easy on neck & wrists

TPE slip-resistant, shock-absorbing inserts on finger & foot contact points on both brake levers and pedals

SPECIFICATIONS

Frame	7005 aluminum triple gauge main tubes and stays, eyeletted stays & dropouts, with fenders
Fork	Jamis suspension, alloy crown and outer legs, 65mm travel
Headset	Sealed, threaded, 1 1/8"
Wheels	Alex single-wall alloy silver anodized rims, 700c, 36H, with Formula alloy QR front and rear hubs, 14g stainless steel spokes
Tires	CST inverted tread design, 700 x 38c, with 3M reflective safety stripe
Derailleurs	Shimano Altus rear, Shimano C051 31.8mm /bottom pull front
Shiftlevers	SRAM Grip-shift MRX-204, 21-speed
Chain	KMC UG-51
Cassette	Shimano freewheel, 7-speed, 13-34
Crankset	Forged alloy crank, 48/38/28 rings, 170mm, with chainguard
BB Set	VP sealed, bolt type, 3SB axle, 68 x 124.5mm (35 - 52 - 37.5)
Pedals	Comfort platform with TPE non-slip insert
Brakeset	Alloy direct pull brakes with Tektro Tenera levers
Handlebar	Hi-rise comfort style, 80mm rise x 640mm wide
Stem	Jamis alloy, angle-adjustable type, 90mm ext x 150mm quill (14.5-17.5") or 110mm ext x 180mm quill (18.5-22")
Grips	SRAM GripShift
Seat Post	Suspension with alloy pillar, 350mm x 27.2mm, with alloy QR clamp
Saddle	Jamis Comfort with synthetic suede top, burnished sides and bumper springs
Sizes	M: 14.5", 16.5", 18.5", 20.5", 22" W: 14.5", 17.5"
Color	Gloss Black (M), Forest Green (M & W) or Violet Mist (W)
Weight	32.30 lbs

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
14.5"	13.46/342	21.50/546	71°	74°	17.52/445	41.30/1049	1.97/50	11.22/285	4.72/120	28.43/722
16.5"	15.12/384	22.11/562	71°	74°	17.52/445	41.93/1065	1.97/50	11.22/285	4.72/120	29.41/747
18.5"	17.32/440	22.48/571	72°	73.5°	17.52/445	41.69/1059	1.97/50	11.22/285	4.72/120	30.75/781
20.5"	19.33/491	23.06/586	72°	73.5°	17.52/445	42.28/1074	1.97/50	11.22/285	5.12/130	32.01/813
22"	20.87/530	23.46/596	72°	73.5°	17.52/445	42.68/1084	1.97/50	11.22/285	5.71/145	33.07/840
14.5"W	9.57/243	21.49/546	71°	74°	17.52/445	41.26/1048	1.97/50	11.22/285	3.94/100	25.55/649
17.5"W	10.31/262	21.88/556	71°	73.5°	17.52/445	41.46/1053	1.97/50	11.22/285	4.33/110	26.14/664