

2009 JAMIS CITIZEN 3



Blue Mist/Stratus Blue

UPGRADES FROM 2008

New hydroformed top and down tube

Vittoria Adventure Touring tires

Shimano New Acera crank

REASONS TO UPGRADE FROM CITIZEN 2

Tektro IO disc brakes

RST Vita TNL fork with lock out

Weinmann ZAC2000 double wall rims with eyelets & black stainless steel spokes

Kalloy 379 suspension seatpost with 45mm travel & MCU damper

Shimano 24-speed EZ Fire plus shifting drivetrain w/ New Deore RD

FEATURES/BENEFITS

Large diameter 700c road bike wheels roll faster & more predictably at speed, and roll over bumps & potholes more comfortably than smaller diameter 26" wheels

Citizen 3's lightweight & durable aluminum frame offers hydroformed top and down tubes & bullet style cable guides for good looks and increased strength

A sloping double diamond frame design in 7 sizes assures best possible customer fit for more comfort, better handling, increased safety

RST's Vita TNL suspension fork features lightweight magnesium sliders, over 2" (60mm) of bump-eating travel, and lock-out to eliminate front-end bobbing during hill climbs

Tektro's IO disc brakes stop great in all conditions & increase wheel longevity by using disc rotors as the braking surface instead of the wheel's rim

Weinmann's ZAC2000 double wall rims with eyelets are stronger, lighter and longer lasting than standard single wall rims

Smooth-rolling, Vittoria Adventure Touring 700 x 38c tires hold more air volume & are more comfortable to ride than smaller width 23 - 28C road tires. These tires also feature a 3M reflective stripe for enhanced visibility in the dark and a puncture-resistant casing that helps protect tubes from flats

Shimano's Alivio EZ-Fire Plus shifters and Deore rear derailleur shift intuitively, smoothly and reliably

The Shimano Acera 48/38/28 crankset & 11-32 cassette provide a huge range of 24-speeds for smooth and easy pedaling on any terrain

Our super plush saddle features memory foam padding for optimum support with maximum comfort. The slip-resistant suede-type top prevents sliding and the burnished side panels reduce leg friction while pedaling. Elastomer springs help soak up high resonant road vibrations. Offered in gender specific sizes.

With nearly 2" of MCU-damped travel, the Citizen 3's suspension seatpost smooths out the road and trail

A long quilled, angle-adjustable stem and 3" rise handlebar offer a comfortable, upright ride position that's easy on neck & wrists

TPE slip-resistant inserts on the Citizen's pedals damp road vibration and provide a more secure connection between foot and pedal

SPECIFICATIONS

Frame	6061 aluminum triple gauge main tubes and stays, sloping design, chanstay disc brake mount, replaceable derailleur hanger, eyeletted dropouts
Fork	RST Vita-TNL suspension, magnesium legs, hydraulic lock out, external preload adjustment, 60mm travel
Headset	Slimstack threaded, Sealed, 1 1/8"
Wheels	Weinmann Zac 2000 double-wall rims with eyelets, 36H, Formula alloy sealed QR front and rear disc compatible hubs, 14g stainless steel spokes
Tires	Vittoria Adventure Touring, 700 x 38c, with Rubber Shielding puncture protection and reflective safety stripe
Derailleurs	Shmano Deore rear, Shimano C102 31.8mm top swing/dual-pull front
Shiftlevers	Shimano Alivio ST-M405 EZ-Fire Plus, 24-speed
Chain	KMC Z82
Cassette	Shimano CS-HG40, 8-speed, 11-32
Crankset	Shimano Acera, 48/38/28, 170mm (14-16.5"), 175mm (18.5-22") with chainguard
BB Set	Sealed cartridge, 68 x 123mm
Pedals	Composite body with steel cage, toe clip attachable.
Brakeset	Tektro IO mechanical disc brakes, 160mm wavy rotors with Shimano Alivio levers
Handlebar	Alloy hi-rise comfort, 40mm rise x 640mm wide
Stem	Satori forged alloy, angle-adjustable, 90mm (14.5/16.5/14.5L/17.5L"), 110mm rise (18.5/20.5/22")
Grips	Kraton for EZ-Fire
Seat Post	Suspension, 45mm travel, 350mm x 27.2mm, alloy clamp with QR seatpin
Saddle	Jamis Comfort with memory foam, synthetic suede top, burnished sides and bumper springs
Sizes	M: 14.5", 16.5", 18.5", 20.5", 22" W: 14.5", 17.5"
Color	Blue Mist/Stratus Blue (M & W)
Weight	33.50 lbs

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
14.5"	13.46/342	21.50/546	71°	74°	17.52/445	41.30/1049	1.97/50	11.22/285	4.72/120	28.43/722
16.5"	15.12/384	22.11/562	71°	74°	17.52/445	41.93/1065	1.97/50	11.22/285	4.72/120	29.41/747
18.5"	17.32/440	22.48/571	72°	73.5°	17.52/445	41.69/1059	1.97/50	11.22/285	4.72/120	30.75/781
20.5"	19.33/491	23.06/586	72°	73.5°	17.52/445	42.28/1074	1.97/50	11.22/285	5.12/130	32.01/813
22"	20.87/530	23.46/596	72°	73.5°	17.52/445	42.68/1084	1.97/50	11.22/285	5.71/145	33.07/840
14.5"W	9.57/243	21.49/546	71°	74°	17.52/445	41.26/1048	1.97/50	11.22/285	3.94/100	25.55/649
17.5"W	10.31/262	21.88/556	71°	73.5°	17.52/445	41.46/1053	1.97/50	11.22/285	4.33/110	26.14/664