

# 2010 CITIZEN 1

## UPGRADES/CHANGES FROM 2009

New rigid fork version

Simpler, lighter and more affordable

New tire design for secure traction and low rolling resistance



Gloss Black



Victory Blue



Pistachio

## FEATURES/BENEFITS

Large diameter 700c road bike wheels roll faster & more predictably at speed and roll over bumps & potholes more comfortably than smaller diameter 26" mountain bike sized wheels.

Citizen's lightweight & durable aluminum frame offers hydroformed top and down tubes & bullet style cable guides for good looks and increased strength.

The sloping double-diamond frame design in 7 sizes assures the best possible customer fit for more comfort, better handling and increased safety.

The Citizen 1's new rigid fork is lighter and simpler than a suspension fork for urban and suburban riding.

CST's new Marathon/Tour tire features a smart tread design for secure grip and low rolling resistance on roads & pathways.

700 x 38c tires hold more air volume & are more comfortable to ride than smaller width 23 - 28C road tires.

Citizen 1's 21-speed twist shifting drivetrain features a full size forged alloy 48/38/28 crankset (with pants guard!), a Shimano Altus rear derailleur and Mega-Range freewheel for easy pedaling up or down hill.

A near all-alloy parts list -- alloy micro-adjust seat post, alloy stem, alloy crank, alloy seat post clamp, alloy hubs, alloy rims, alloy brakes & levers, alloy kickstand -- reduces weight, adds value and is rust-proof.

We offer super plush comfort saddles with slip resistant suede-type top, "thigh glide" burnished sides, elastomer springs -- with male & female specific saddle lengths & widths.

Our telescoping suspension seat post with 1" of coil-sprung travel smooths out the road and trail.

The long quilled, angle-adjustable stem and 3" rise handlebars offer a comfortable, upright ride position that's easy on neck & wrists.

TPE slip-resistant, shock-absorbing inserts on finger & foot contact points on both brake levers and pedals help Citizen deliver a comfortable and secure workout.

## SPECIFICATIONS

Frame	6061 aluminum triple gauge main tubes and stays, sloping design, replaceable derailleur hanger, eyeletted dropouts
Fork	Hi-tensile steel unicrown, straight blades, with dropout eyelets
Headset	Sealed, threaded, 11/8"
Wheels	Alex single-wall alloy silver anodized rims, 36H, Formula alloy hubs with QR, 14g stainless steel spokes
Tires	CST Marathon/Tour, 700 x 38c, with silver safety stripe
Derailleurs	Shimano Altus RD-M310 rear and Shimano FD-TX51 front, 31.8mm, top swing/dual pull front.
Shiftlevers	Shimano Revo-Shift, SL-RS43, 21-speed
Chain	KMC UG-51
Cassette	Shimano TZ-31 freewheel, 7-speed, 14-34
Crankset	Forged alloy crankset, 48/38/28T, 170mm with chainguard
BB Set	VP sealed, 3PB bolt type axle, 35-52-32, 119mm
Pedals	Comfort platform style with TPE non-slip insert
Brakeset	Alloy linear-pull brakes with Tektro Tenera levers
Handlebar	Comfort hi-rise, 80mm rise x 640mm width
Stem	Jamis alloy, angle-adjustable type, 90mm ext x 150mm quill (14-17") or 110mm ext x 180mm quill (18-23")
Grips	Dual compound kraton, for twist shift
Seat Post	Suspension with alloy pillar, 350mm x 27.2mm, with alloy QR clamp
Saddle	Jamis Comfort with synthetic suede top, burnished sides and bumper springs
Sizes	M: 15", 17", 19", 21", 23" W: 14", 18"
Color	Gloss Black (M), Victory Blue (M & F), Pistachio (F)

## GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
15"	13.46/342	21.50/546	71°	74°	17.52/445	41.30/1049	1.97/50	11.22/285	4.72/120	28.43/722
17"	15.12/384	22.11/562	71°	74°	17.52/445	41.93/1065	1.97/50	11.22/285	4.72/120	29.41/747
19"	17.32/440	22.48/571	72°	73.5°	17.52/445	41.69/1059	1.97/50	11.22/285	4.72/120	30.75/781
21"	19.33/491	23.06/586	72°	73.5°	17.52/445	42.28/1074	1.97/50	11.22/285	5.12/130	32.01/813
23"	20.87/530	23.46/596	72°	73.5°	17.52/445	42.68/1084	1.97/50	11.22/285	5.71/145	33.07/840
14" F	9.57/243	21.49/546	71°	74°	17.52/445	41.26/1048	1.97/50	11.22/285	3.94/100	25.55/649
18" F	10.31/262	21.88/556	71°	73.5°	17.52/445	41.46/1053	1.97/50	11.22/285	4.33/110	26.14/664