

# 2010 DAKAR XCT 1

## UPGRADES/CHANGES FROM 2009

NEW stronger/stiffer chainstay and yoke

Suntour SF9-EPICON LOD 15QLC fork

Hayes Stroker Ryde brakes

FSA ZS-3 headset

DT Swiss Champion spokes

Jamis lock-on dual-density grips



Blue Smoke

## FEATURES/BENEFITS

The XCT's mp<sup>3</sup> multi-link suspension design is optimized to shed weight, keep a low center of gravity and offer superb pedaling efficiency. It includes 10mm shock hardware for increased lateral & torsional stiffness and enhanced rear shock durability and performance.

Our double-butted top tube is sloped & bent for the increased standover that aggressive trail riding requires. The bend in the down tube is designed to accommodate the 200mm/50mm stroke rear shock. It just happens to look really good with that bent top tube.

The XCT 1's fully-active 130mm travel is controlled by a Rock Shox Bar 2.1 rear air spring shock. This single air valve design with pre-set negative air pressure and large positive air chamber features a hydraulically damped rebound system with internal floating piston that's externally adjustable for fine tuning ride characteristics.

SR/SunTour's Epicon suspension fork offers a 15mm front axle, Mag lowers with air spring, hydraulic speed lock-out, and externally adjustable rebound damping. Look closely at the 15mm QR. It's the coolest front axle ever!

Hayes Stroker Ryde hydraulic disc brakes were designed with insulated caliper pistons to control fluid temperature eliminating lever fluctuation & provide a reliable feel every ride, all conditions.

Shimano's new SLX Shadow derailleur features a quiet super low-profile design that won't slap the chainstay in rough riding conditions. Direct cable routing reduces the risk of housing snag.

The Shadow derailleur also features a stronger return spring that delivers positive, crisp shifts. It was clearly designed specifically for the rigors of aggressive trail riding.

The Saguaro tires from Geax ride exceptionally fast, with low rolling resistance, thanks to the central ridge of uninterrupted knobs.

WTB's Rocket V saddle features a uniquely contoured pad shape helping to increase power output by properly angling & positioning the sit bones.

DT Swiss Champion spokes are exactly that: a Champion. These classic, strong, long lasting spokes are made of high grade CrNi 18/10 stainless, are cold forged to shape and feature rolled threads for superior strength & smoothness.

Jamis new Lock-On dual-density grips offer a solid feel with lock-on, no-slip security.

## SPECIFICATIONS

Frame	Kinesium alloy main triangle, STW weight optimized 7005 seat & chainstays, 130mm travel mp3 linkage design, cartridge bearing pivots, Rock Shox Bar 2.1 shock with 10mm hardware, replaceable derailleur hanger
Fork	Suntour SF9-EPICON LOD 15, air spring, hydraulic Speed-lock with external rebound damping, 32mm stanchions, 140mm travel
Headset	FSA ZS-3 semi-integrated with 20mm shim stack, 1 1/8"
Wheels	Alex DP17 disc-specific rims, 32H, eyeletted, Formula alloy front and rear disc hubs, DT Swiss Champion 2.0mm stainless steel spokes and nickel-plated brass nipples
Tires	Geax Saguaro, 26 x 2.0"
Derailleurs	Shimano SLX Shadow rear and Deore 34.9mm top pull front
Shiftlevers	Shimano Deore Shadow Rapidfire Plus, 27-speed
Chain	KMC Z9000
Cassette	SRAM Powerglide 950, 9-speed, 11-34
Crankset	FSA AlphaDrive, 44/32/22, 170mm (13-15"), 175mm (17-21")
BB Set	FSA PowerDrive, splined, 73 x 121mm
Pedals	Flatbed alloy platform with pedal spikes
Brakeset	Hayes Stroker Ryde hydraulic disc brakes with V6 rotors
Handlebar	Ritchey Mountain Rizer, 31.8 OD x 20mm rise x 670mm
Stem	Ritchey 4-bolt OS, 31.8 bar bore x 6D rise x 90mm (13-15"), 100mm (17-19") & 120mm (21")
Grips	Jamis Lock-On, dual density
Seat Post	Ritchey 2B OS, 31.6 x 350mm with alloy clamp and cromo seatpin
Saddle	WTB Rocket V Comp with SL cover
Sizes	13", 15", 17", 19", 21"
Color	Blue Smoke

## GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
13"	12.32/313	21.22/539	67.5°	73.5°	17.12/435	42.36/1076	1.49/38	12.95/329	4.53/115	29.09/739
15"	13.74/349	22.12/562	67.5°	73°	17.12/435	43.07/1094	1.49/38	12.95/329	4.53/115	29.80/757
17"	15.67/398	22.79/579	67.5°	73°	17.12/435	43.74/1111	1.49/38	12.95/329	4.72/120	30.86/784
19"	17.60/447	23.70/602	67.5°	73°	17.12/435	44.68/1135	1.49/38	12.95/329	5.51/140	32.16/817
21"	19.60/498	24.08/612	67.5°	72.5°	17.12/435	44.88/1140	1.49/38	12.95/329	5.90/150	33.19/843