



Pearl White

UPGRADES/CHANGES FROM 2009

- Geax Gato 2.3" tires
- Alex TD25 disc-specific rims
- Shimano FD-M360 front derailleur

FEATURES/BENEFITS

This frame lives up to the Komodo name: stout Kinesis-manufactured 7005 tubing, double-gusseted, with massive 57mm down tube ovalized to 72mm at the head tube for impressive frontal strength

A 35mm seat tube with 31.6mm seat post assures the stiffest possible pedaling & steering platform, with a sloping rifled top tube for low stand-over

RST's Launch T suspension fork offers 130mm of coil-sprung/MCU-damped suspension travel with external preload adjuster & stout 32mm stanchions

FSA's new DynaDrive crank with 32/22T chainrings offers a polycarbonate bash guard to protect the rings and a splined PowerDrive BB interface for greater crank strength & rigidity

Tektro's IO disc brakes stop great in all conditions & increase wheel longevity by eliminating the rim sidewall from the brake system

Disc hubs twist when disc brake calipers hub rotors during stops. This hub twisting increases "pull" load on the nipples in the spoke bed. The Alex TD25 spoke bed is cleverly reinforced to resist disc brake torque and prevent spokes & nipples from shearing at the spoke bed.

Our over-sized diameter riser bar and stem combination offers extra-stiffness, strength and durability.

WTB's Speed V Sport SE Saddle features a soft elastomer shell with a deep padding set to provide maximum comfort.

The Komodo's Geax Gato tires offer very low rolling resistance and predictable handling. They can hold a line in the sharpest of corners, thanks to the reinforced sidewalls.

SPECIFICATIONS

Frame	7005 triple gauge aluminum main tubes, 1.5" head tube, gusseted main frame, heavy-duty stays, rifled top tube & replaceable derailleur hanger
Fork	RST Launch T, external preload adjuster, 32mm steel stanchions, 130mm travel, coil spring with MCU bottom-out
Headset	Zero-Stack internal cup, 20mm shim stack, with 1.5" to 1-1/8" reducer
Wheels	Alex TD-25 disc-specific rims with reinforced spoke bed, Formula 6-bolt disc hubs, 14g black stainless steel spokes
Tires	Geax Gato, 26 x 2.3"
Derailleurs	SRAM SX-4 rear mid-cage, Shimano Acera 34.9mm dual pull front
Shiftlevers	SRAM SX-4 Uni-lever trigger-shift, 16-speed
Chain	KMC Z82
Cassette	Shimano HG40, 8-speed, 11-32
Crankset	FSA DynaDrive, 32/22, with polycarbonate bash guard, 170mm (all frame sizes)
BB Set	FSA Powerdrive, sealed cartridge, 73 x 118mm
Pedals	Flatbed alloy platform type with pedal spikes
Brakeset	Tektro IO mechanical disc brakes, ML-330 levers and 160mm wavy rotors
Handlebar	Jamis DJ 6061 T-6 riser bar, 31.8 OD x 86mm rise x 640mm
Stem	Jamis DJ alloy 4-bolt bar clamp threadless, 31.8 bar bore x 30D rise x 50mm
Grips	WTB Moto-Grip, medium diameter
Seat Post	Jamis OS alloy micro-adjust, 31.6x 350mm with alloy QR clamp
Saddle	WTB Speed V Sport SE with SL cover
Sizes	S, M, L
Color	Pearl White

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
S	12.52/318	22.48/571	68.5°	71.48°	16.14/410	41.81/1062	1.50/38	13.46/342	5.12/130	27.16/690
M	14.09/358	23.50/597	68.5°	71.48°	16.14/410	42.79/1087	1.50/38	13.46/342	5.12/130	27.99/711
L	15.98/406	24.41/620	68.5°	71.48°	16.14/410	43.70/1110	1.50/38	13.46/342	5.51/140	28.97/736