

2010 KOMODO II

UPGRADES/CHANGES FROM 2009

Shimano SLX Shadow rear & Acera front derailleurs

Geax Gato 2.3" tires

Alex TD25 disc-specific rims

Shimano Acera front derailleur

REASONS TO UPGRADE FROM KOMODO 1

Marzocchi Dirt Jumper Fork

Formula sealed cartridge 20mm thru-axle front hub

Hayes Stroker Ryde hydraulic brakes

185mm front rotor

Shimano SLX rear derailleur

FSA StepUp crank



Purple Haze

FEATURES/BENEFITS

Go dirt jumping, take it on an urban assault mission, hop around the rocks, take it to the trail or ride it to school: this bike is the perfect tool.

This frame lives up to the Komodo name: stout Kinesis-manufactured 7005 tubing, double-gusseted, with massive 57mm down tube ovalized to 72mm at the head tube for impressive frontal strength

A 35mm seat tube with 31.6mm seat post assures the stiffest possible pedaling & steering platform, with a sloping rifled top tube for low stand-over

"Marzocchi Dirt Jumper 1" fork says it all: 32mm aluminum stanchions, 100mm of travel with a 20mm thru-axle and suspension that carries the Marzocchi name

Shimano's SLX Shadow derailleur features a QUIET super low-profile design that won't slap the chainstay in rough riding conditions. Direct cable routing reduces the risk of housing snag.

The Shadow derailleur features a stronger return spring that delivers positive, crisp shifts. It was clearly designed specifically for the rigors of aggressive trail riding.

FSA's FSA StepUp crank with ISIS splined BB, 32/22T heat-treated rings and 170mm crank arms with chromoly pedal inserts delivers the pedaling-platform confidence DJ riders demand.

Hayes Stroker Ryde hydraulic disc brakes were designed with insulated caliper pistons to control fluid temperature eliminating lever fluctuation & provide a reliable feel every ride, all conditions

The large brake pads yield optimal heat management and, in tandem with the V7 185mm rotor up front & V6 rotor in back, deliver lots of stopped power.

WTB's Speed V Sport SE Saddle features a soft elastomer shell with a deep padding set to provide maximum comfort

The Komodo's Geax Gato tires offer very low rolling resistance and predictable handling. They can hold a line in the sharpest of corners, thanks to the reinforced sidewalls.

SPECIFICATIONS

Frame	7005 triple gauge aluminum main tubes, 1.5" head tube, gusseted main frame, heavy-duty stays, rifled top tube, replaceable derailleur hanger
Fork	Marzocchi Dirt Jumper 1, 32mm aluminum stanchions, 20mm thru-axle, rebound damping adjuster, air preload, 100mm travel
Headset	Zero-Stack internal cup, 20mm shim stack, with 1.5" to 1-1/8" reducer
Wheels	Alex TD-25 disc specific rims with reinforced spoke bed, Formula 20mm thru-axle sealed bearing front and sealed cup & cone rear disc hubs, 14g black stainless steel spokes
Tires	Geax Gato, 26 x 2.3"
Derailleurs	Shimano SLX Shadow rear and Acera 34.9mm dual pull front
Shiftlevers	Shimano Alivio Rapidfire SL, 16-speed
Chain	KMC Z82
Cassette	Shimano HG40, 8-speed, 11-32
Crankset	FSA Step-Up, 32/22, with polycarbonate bash guard, 170mm (all frame sizes)
BB Set	FSA ISIS, sealed cartridge, 73 x 118mm
Pedals	Flatbed alloy platform type with pedal spikes
Brakeset	Hayes Stroker Ryde hydraulic disc brakes with V7 front and V6 rear rotors
Handlebar	Jamis DJ 6061 T-6 riser bar, 31.8 OD x 86mm rise x 640mm
Stem	Jamis DJ alloy 4-bolt bar clamp threadless, 31.8 bar bore x 30D rise x 50mm
Grips	WTB Weirwolf, dual DNA compound
Seat Post	Jamis OS alloy micro-adjust, 31.6 x 350mm with alloy QR clamp
Saddle	WTB Speed V Sport SE with SL cover
Sizes	S, M, L
Color	Purple Haze

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
S	12.52/318	22.48/571	68.5°	71.48°	16.14/410	41.81/1062	1.50/38	13.46/342	5.12/130	27.16/690
M	14.09/358	23.50/597	68.5°	71.48°	16.14/410	42.79/1087	1.50/38	13.46/342	5.12/130	27.99/711
L	15.98/406	24.41/620	68.5°	71.48°	16.14/410	43.70/1110	1.50/38	13.46/342	5.51/140	28.97/736