



Victory Blue/Pearl White



Gloss Black/Cool Grey White



Sugar Blue/Pearl White

FEATURES/BENEFITS

Trail X2's frame is made of lightweight-but-strong 7005 series aluminum tubing, featuring over-sized, ovalized & tapered tubing for increased frame strength

The sloping Enduro II frame design is offered in 8 (!) sizes, assuring the best possible customer fit for optimal handling and enhanced comfort

Our smallest 12" & 13" frames are especially suitable for junior riders. These frame sizes can comfortably & safely fit taller kids as young as 9 or 10. With the Trail X's larger diameter 26" wheels and 300mm seat post (with saddle-height-adjusting quick-release clamp), this bike will last them for years!

The RST 191-T suspension fork delivers 80mm of coil-sprung telescoping travel with an MCU elastomer bumper that smooths fork bottom-out should it occur. With a lightweight alloy crown and stout 28.6mm steel stanchions for stiffness & strength and a straight-tracking front wheel, this fork will deliver smooth, controlled rides weekend after weekend.

Disc hubs twist during braking. This twisting increases "pull" load on the nipples in the spoke bed. The Alex TD25 spoke bed is cleverly reinforced to resist disc brake torque and prevent spokes & nipples from shearing at the spoke bed.

Disc brakes stop great in all conditions, wet - dry - muddy - snowy, & increase wheel longevity by eliminating the rim sidewall from the brake system.

The X2's 21-speed Shimano EZ-Fire Plus drivetrain features a Shimano Acera rear derailleur, alloy 42/34/24 crankset & Shimano 14-28 indexed freewheel for smooth shifting, easy climbing & secure descents.

Headset's patented threadless steering system not only saves weight, but pre-loading the headset bearings for optimal steering precision is much easier than on standard threaded headsets.

Sealed cartridge bottom brackets reduce maintenance time and expense.

The 26 x 1.95" XC knobbies on our Trail X-series bikes are from the same manufacturer that produces Maxxis tires: one of the most respected names in off-road rubber in the business.

The Trail X-series broad-based ATB saddle with front & rear protective guards offers plenty of comfort, durability & style.

UPGRADES/CHANGES FROM 2009

Frame features optimized disc brake housing length & cradle positioning

RST 191-T fork with MCU/coil spring internals, 80mm travel & external preload adjustor

Shimano Acera RD-M360 rear derailleur & SIS 14-34T freewheel

Alex TD-25 disc-specific double-wall rims

REASONS TO UPGRADE FROM TRAIL X1

RST 191-T fork with MCU/coil spring internals, 80mm travel & external preload adjustor

Bengal M606 mechanical disc brakes

Alex TD-25 disc-specific double-wall rims & alloy disc hubs

Shimano Acera RD-M360 rear derailleur

Sealed cartridge bottom bracket

SPECIFICATIONS

Frame	Enduro II frame design, 7005 aluminum main tubes, replaceable derailleur hanger
Fork	RST 191-T, alloy crown, MCU/coil spring with external preload adjustor, 80mm travel
Headset	VP threadless with 20mm shim stack. 1 1/8"
Wheels	Alex TD-25 disc-specific rims with reinforced spoke bed, 32H alloy disc hubs with QR, 14g nickel-plated spokes
Tires	CST XC knobbie, 26" x 1.95"
Derailleurs	Shimano Acera M360 rear and TZ30 31.8mm top pull front
Shiftlevers	Shimano Acera ST-EF50 EZ-Fire Plus, 21-speed
Chain	KMC Z51
Cassette	Shimano SIS 7-speed freewheel, 14-34T
Crankset	Forged SR Suntour alloy crank arms, 42/34/24 rings, 170mm
BB Set	Sealed cartridge, 68 x 122.5mm
Pedals	ATB platform, hi-impact resin cage & body
Brakeset	Tektro lo mechanical disc brakes and Shimano levers
Handlebar	Jamis XC riser, 6D sweep x 13mm rise x 620mm wide
Stem	Jamis XC alloy threadless, 10D rise, 90mm (12-14"), 100mm (15.5-17"), 120mm (19-21")
Grips	Kraton for trigger-shift
Seat Post	Jamis alloy micro-adjust, 27.2 x 300mm, with alloy QR clamp
Saddle	Jamis ATB with pressure relief channel, SL cover, protective front and rear guards
Sizes	M: 13", 15", 17", 19", 21" F: 12", 14", 18"
Color	M: Gloss Black/Cool Grey or Victory Blue/Pearl White F: Sugar Blue/Pearl White

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
13"	9.29/236	20.86/530	70.5°	74°	16.73/425	40.43/1027	1.77/45	12.08/307	4.13/105	25.90/658
15"	12.20/310	21.42/544	70.5°	74°	16.73/425	41.02/1042	1.77/45	12.08/307	4.72/120	28.03/712
17"	13.50/343	21.89/556	71°	73.5°	16.73/425	41.06/1043	1.77/45	12.08/307	4.92/125	28.86/733
19"	15.51/394	22.52/572	71°	73.5°	16.73/425	41.69/1059	1.77/45	12.08/307	5.12/130	30.16/766
21"	17.36/441	23.34/593	71.5°	73°	16.73/425	42.17/1071	1.77/45	12.08/307	6.49/165	31.77/807
12" F	7.95/202	20.51/521	70.5°	74°	16.93/430	40.28/1023	1.77/45	12.08/307	4.13/105	24.92/633
14" F	8.66/220	20.71/526	70°	73°	16.93/430	40.31/1024	1.77/45	12.08/307	4.92/125	25.51/648
18" F	8.97/228	21.97/558	70.5°	72.5°	16.93/430	41.18/1046	1.77/45	12.08/307	5.51/140	25.82/656