

UPGRADES/CHANGES FROM 2009

Already as good as it gets for this level



Stainless



Reef Blue



Ocean Mist

FEATURES/BENEFITS

The Trail XR is an IBD-quality, low-maintenance utility bike with a price tag almost anyone can live with. Perfect for college or job commuting during the week and a fitness ride on the weekend.

Trail XR's frame is made of high strength, hi-tensile steel and features over-sized, ovalized & tapered tubing for increased frame strength and great looks.

Our smallest 12" & 13" frames are especially suitable for junior riders. These frame sizes can comfortably & safely fit taller kids as young as 9 or 10. With the Trail X's larger diameter 26" wheels and 300mm seat post (with saddle-height-adjusting quick-release clamp), this bike will last them for years!

With the Trail X's larger diameter 26" wheels and 300mm seat post with quick-release clamp, this bike will last them for years

Our straight-bladed tubular unicrown fork is significantly lighter than any suspension fork, offering more responsive steering and an easier to lift-up-the-dorm-stairs bike.

Sram mid cage X3 rear derailleur overs quick solid shifts and reliability

XR's 21-speed SRAM twsit-shift drivetrain shifts intuitively and smoothly. With 3 chainrings up front and a 13-28 indexed freewheel in back, steep hills are flattened and fun.

Not so long ago, V-brakes were the most powerful bike brakes known to man. Then disc brakes came along. No biggie. V-brakes will still lock up your wheels & stop you safely.

Every Trail XR offers quick release front & rear wheels and a quick release saddle assembly to make make transport, storage, or locking up a snap.

That long-quilled, hi-rise stem positions the XR riser up higher than our other Trail X series bikes with threadless steering systems for a more propped-up, less-weight-on-the-wrists riding position. Handlebar height can be adjusted by loosening the stem quill bolt and moving the stem up or down.

The 26 x 1.95" XC knobbies on our Trail X-series bikes are from the same manufacturer that produces Maxxis tires: one of the most respected names in off-road rubber in the business.

The Trail X-series broad-based ATB saddle with front & rear protective guards offers plenty of comfort, durability & style.

There's lots of lightweight, rust-proof alloy parts on the XR -- micro-adjust seat post, crank, seat post clamp, rims and brakes -- that make riding more pleasurable & requires much less maintenance to keep oxidation free.

SPECIFICATIONS

Frame	Enduro II frame design, hi-tensile carbon steel tubes
Fork	XC Suspension fork, alloy crown, coil spring, 60mm travel
Headset	VP threaded type, 11/8"
Wheels	Alloy 26 x 1.50" 36H rims, heavy-duty ATB hubs with QR, 14g nickel-plated spokes
Tires	CST ATB, 26 x 1.95", blackwall
Derailleurs	SRAM X rear and Shimano TZ30 31.8mm top pull front
Shiftlevers	SRAM 3.0 1:1 Grip Shift, 21-speed
Chain	KMC Z51
Cassette	Indexed 7-speed freewheel, 13-28
Crankset	Forged alloy crank, 42/34/24 steel rings, 170mm
BB Set	VP bolt type 3SB axle, 68 x 124.5mm (35 - 52 - 37.5)
Pedals	ATB platform, hi-impact resin, toe clip attachable
Brakeset	Alloy linear pull type with Shimano alloy levers
Handlebar	Jamis XC riser, 6D sweep x 13mm rise x 620mm wide
Stem	Jamis hi-rise, 40D rise x 90mm (12-14"), 100mm (16-18"), 120mm (19-21")
Grips	Kraton for Grip Shift.
Seat Post	Jamis alloy micro-adjust, 28.6 x 300mm, with alloy QR clamp
Saddle	Jamis ATB with pressure relief channel, SL cover, protective front and rear guards
Sizes	M: 13", 15", 17", 19", 21" F: 12", 14", 18"
Color	M: Stainless or Reef Blue F: Ocean Mist

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
13"	9.53/242	21.02/534	70.5°	74°	16.73/425	40.43/1027	1.77/45	12.08/307	4.13/105	25.63/651
15"	12.16/309	21.57/548	70.5°	74°	16.73/425	41.02/1042	1.77/45	12.08/307	4.72/120	27.52/699
17"	13.43/341	21.97/558	71°	73.5°	16.73/425	41.06/1043	1.77/45	12.08/307	4.92/125	28.34/720
19"	15.47/393	22.60/574	71°	73.5°	16.73/425	41.69/1059	1.77/45	12.08/307	5.12/130	29.60/752
21"	17.32/440	23.42/595	71.5°	73°	16.73/425	42.17/1071	1.77/45	12.08/307	6.49/165	31.18/792
12" F	7.91/201	20.63/524	70.5°	74°	16.93/430	40.28/1023	1.77/45	12.08/307	4.13/105	24.53/623
14" F	8.58/218	20.82/529	70°	73°	16.93/430	40.31/1024	1.77/45	12.08/307	4.92/125	25.12/638
18" F	8.94/227	22.05/560	70.5°	72.5°	16.93/430	41.18/1046	1.77/45	12.08/307	5.51/140	25.47/647