



Monterey Blue



Ano Grey



Pearl White

UPGRADES/CHANGES FROM 2010

New Enduro III frame design

FEATURES/BENEFITS

The Trail XR is an IBD-quality, low-maintenance utility bike with a price tag most can live with: perfect for college or job commuting during the week and a fitness ride on the weekend.

Trail XR's frame is made of high strength, hi-tensile steel and features over-sized, ovalized & tapered tubing for increased frame strength.

The sloping Enduro III frame design is offered in 8 sizes, assuring the best possible customer fit for optimal handling and enhanced comfort.

Our smallest 12" frame size is especially suitable for junior riders. This frame size can comfortably & safely fit taller kids as young as 9 or 10. With the Trail X's larger diameter 26" wheels and 300mm seat post with quick-release clamp, this bike will last them for years.

Our straight-bladed tubular unicrown fork is significantly lighter than a suspension fork, offering more responsive steering and an easier to lift-up-the-dorm-stairs bike.

SRAM's mid cage X3 rear derailleurs offers quick, solid shifts reliably. A great value for beginners or light adventurers.

XR's 21-speed SRAM twist-shift drivetrain shifts intuitively and smoothly. With 3 chainrings up front and a 13-28 indexed freewheel in back, steep hills are flattened and fun.

Not so long ago, V-brakes were the most powerful bike brakes known to man. Then disc brakes came along. No biggie. V-brakes will still lock up your wheels & stop you safely. And they don't weigh as much as discs!

Every Trail XR offers quick release front & rear wheels and a quick release saddle assembly to make transport, storage, or locking up a snap.

That long-quilled, hi-rise stem positions the XR riser handlebar higher than on our other Trail series bikes with threadless steering systems for a more propped-up, less-weight-on-the-wrists riding position.

The 26 x 1.95" XC knobbies on our Trail X-series bikes are from the same manufacturer that produces Maxxis tires: one of the most respected names in off-road rubber in the business.

The Trail X-series ATB saddle with front & rear protective guards offers plenty of comfort, durability & style.

There's lots of lightweight, rust-proof alloy parts on the XR -- micro-adjust seat post, crank, seat post clamp, rims and brakes -- that make riding more pleasurable & maintenance easier.

SPECIFICATIONS

Frame	Enduro III frame design, hi-tensile carbon steel tubes, radiused top tube, extended seat mast with brace
Fork	Unicrown, hi-tensile steel, with over-sized radiused blades
Headset	VP threaded type, 1 1/8"
Wheels	Alloy 26 x 1.50" 36H rims, heavy-duty ATB hubs with QR, 14g black electro-plated spokes
Tires	CST ATB, 26 x 1.95"
Derailleurs	SRAM X rear and Shimano TZ30 31.8mm top pull front
Shiftlevers	SRAM 3.0 1:1 Grip Shift, 21-speed
Chain:	KMC Z51
Cassette	Indexed 7-speed freewheel, 13-28
Crankset	Forged alloy crank, 42/34/24 steel rings, 170mm
BB Set	VP bolt type 3SB axle, 68 x 124.5mm
Pedals	ATB platform, hi-impact resin cage & body
Brakeset	Alloy linear pull type with full alloy 4-finger levers
Handlebar	Jamis XC riser, 6° sweep x 13mm rise x 620mm
Stem	Jamis hi-rise, 40° rise x 90mm (12-15"), 100mm (17-18"), 110mm (19"), 120mm (21")
Grips	Kraton for Grip Shift.
Seatpost	Jamis alloy micro-adjust, 28.6 x 300mm, with alloy QR clamp
Saddle	Jamis ATB with pressure relief channel, SL cover, protective front and rear guards
Sizes	M: 13", 15", 17", 19", 21" F: 12", 14", 18"
Colors	M: Monterey Blue or Ano Grey F: Pearl White

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
13"	9.29/236	20.86/530	70.5°	74°	16.73/425	40.35/1025	1.77/45	12.08/307	4.13/105	25.79/655
15"	12.28/312	21.42/544	70.5°	74°	16.73/425	40.90/1039	1.77/45	12.08/307	4.72/120	27.91/709
17"	13.34/339	21.89/556	71°	73.5°	16.73/425	40.98/1041	1.77/45	12.08/307	4.92/125	28.66/728
19"	15.39/391	22.52/572	71°	73.5°	16.73/425	41.65/1058	1.77/45	12.08/307	5.12/130	30.00/762
21"	16.81/427	23.34/593	71.5°	73°	16.73/425	42.12/1070	1.77/45	12.08/307	6.49/165	31.45/799
12" F	7.95/202	20.51/521	70.5°	74°	16.93/430	40.16/1020	1.77/45	12.08/307	4.13/105	24.92/633
14" F	8.66/220	20.71/526	70°	73°	16.93/430	40.23/1022	1.77/45	12.08/307	4.92/125	25.67/652
18" F	8.97/228	21.97/558	70.5°	72.5°	16.93/430	41.10/1044	1.77/45	12.08/307	5.51/140	25.98/660