

2016 EXPLORER 1



Gloss Black



Blueberry

SPECIFICATIONS

Frame	Sport comfort design, hi-tensile steel with low-standover/upright ride position, center-mount kickstand bracket
Fork	Coil-spring suspension, alloy crown, chrome-plated stanchions, mini boots, 60mm travel
Headset	ATB sealed, threaded, 1 1/8"
Wheels	Alex C-1000 alloy rims, 36H, with Formula alloy hubs, QR front and rear, 14g stainless steel spokes
Tires	Jamis Sport Comfort, 26 x 1.95", blackwall
Derailleurs	SRAM X rear, Shimano M191 31.8mm top swing/dual pull front
Shiftlevers	SRAM 3.0 Comp ESP twist-shift, 21-speed
Chain	KMC UG51
Cassette	Shimano freewheel 7-speed, 14-34
Crankset	SR XCC alloy crank with 48/38/28 chainrings, 170mm crank length, with chain-guard
BB Set	VP sealed bolt type, 3RB axle, 68 x 129mm (35-52-42)
Pedals	Comfort platform with TPE non-slip insert
Brakeset	ProMax alloy direct pull brakes with Tektro Tenera levers
Handlebar	Hi-rise comfort, 15D sweep x 80mm rise x 640mm wide
Stem	Jamis alloy, angle-adjustable, 90mm ext x 150mm quill (13.5-17.5") or 110mm ext x 180mm quill (18-21")
Grips	Kraton comfort
Seat Post	Suspension, alloy micro-adjust, 350mm x 25.4mm, with alloy QR clamp
Saddle	Jamis Comfort with extra thick padding, synthetic suede top, burnished side panels and bumper springs
Sizes	M: S (13"), M (15"), L (18"), XL (21") S/T: S (14"), M (17")
Color	M: Blueberry or Gloss Black S/T: Blueberry or Pure White

UPGRADES/CHANGES FROM 2015

Same quality Jamis specification as 2015

TOP 5 THINGS YOU NEED TO KNOW

The Explorer 1's hi-tensile steel frame, while heavier than more expensive aluminum, rides smoother & more comfortably than aluminum thanks to the natural shock damping qualities of steel.

Explorer 1 features a 21-speed SRAM 3.0 twist-shifting drivetrain with triple-ring SR XCC 48/38/28 crankset, Shimano Altus front derailleur & 14-34 Mega-Range freewheel for easy hill climbing and controlled pedaling descents.

The Explorer's suspension fork delivers over 2" of bump-eating, coil sprung suspension with alloy crown, stout 28mm stanchions and mini-boots to protect sliders. The seatpost offers 1" of coil-sprung telescoping travel too, to smooth out the road and trail.

Tektro's CL530 brake levers offer slip-resistant, shock-absorbing inserts on the finger contact points for more secure, comfortable braking

Our long quilled, angle-adjustable stem and 3" rise handlebars offer a supremely comfortable, upright ride position that's easy on neck & wrists.

RECREATION - Comfort

GEOMETRY

SIZE	CENTER of BB to TOP of TT	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
S	11.30 / 287	21.06 / 535	68.39°	70.39°	16.73 / 425	40.12 / 1019	1.77 / 45	12.09 / 307	4.72 / 120	27.20 / 691
M	13.31 / 338	21.65 / 550	68.40°	70.40°	16.73 / 425	40.75 / 1035	1.77 / 45	12.09 / 307	5.51 / 140	28.78 / 731
L	15.79 / 401	22.64 / 575	68.42°	70.42°	16.73 / 425	41.77 / 1061	1.77 / 45	12.09 / 307	6.89 / 175	30.79 / 782
XL	18.78 / 477	23.43 / 595	68.44°	70.44°	16.73 / 425	42.60 / 1082	1.77 / 45	12.09 / 307	8.27 / 210	33.07 / 840
S S/T	5.79 / 147	20.67 / 525	68.39°	70.39°	16.93 / 430	39.96 / 1015	1.77 / 45	12.09 / 307	6.30 / 160	17.87 / 454
M S/T	7.05 / 179	22.05 / 560	68.39°	70.41°	16.93 / 430	41.42 / 1052	1.77 / 45	12.09 / 307	6.89 / 175	18.74 / 476