



Inferno

SPECIFICATIONS

Frame	Jamis Road Dyad Plus T700/FRP mono-coque carbon fiber frame, FEA optimized Near Net SPV molding process, formed top and down tubes with SST tubing diameters, oversized tapered seat tube, 1 1/8" - 1.5" head tube with carbon bearing races, EVO386 carbon BB shell, ACE internal cable routing compatible for both Di2 wires or traditional cables, rider tuned twin seat stays with spoiler bridge, oversized asymmetrical chainstays with direct mount brakes, carbon dropouts with replaceable alloy FD mount and RD hanger.
Fork	Jamis Road carbon composite fork, FEA optimized Near Net SPV molding process, 1.5" hollow formed crown, mono-coque one-piece forming technology, carbon dropouts with stainless axle interfaces
Headset	Ritchey Pro Drop-In, sealed bearing with nylon upper compression ring, 1 1/8" - 1.5"
Wheels	Mavic Aksium Race 11-Speed wheelset, 20H, 24mm rim profile with UB Control and H2 technology, Mavic alloy hubs with QRM bearings and FTS-L freehub and self-locking straight pull aerodynamic spokes
Tires	Vittoria Zaffiro Pro Slick, 700 x 23c, folding
Derailleurs	Shimano Dura Ace RD-9000 rear and Ultegra FD-6800 braze-on
Shiftlevers	Shimano Ultegra ST-6800 Dual Control STI, 22-Speed
Chain	Shimano CN-HG700 11-Speed
Cassette	Shimano Ultegra CS-6800 11-Speed 11-28T
Crankset	Shimano Ultegra FC-6800 compact double, 52/36T, 170mm (48/51), 172.5mm (54/56), 175mm (58/61)
BB Set	Enduro PressFit 30 and Wheels MFG EVO adaptors
Pedals	N/A
Brakeset	Shimano BR-6010 direct mount rear and BR-6800 dual pivot front calipers with Shimano Ultegra ST-6800 STI brake levers
Handlebar	Ritchey Comp Logic Curve, 6061 double-buttet aluminum, 31.8 x 400mm (48/51), 420mm (54/56), 440mm (58/61)
Stem	Ritchey Comp 4-Axis, 3D net forged 6061 alloy, 6" x 90mm (48/51), 100mm (54/56), 120mm (58/61)
Grips	Fizik Superlight Microsoft Touch with Fizik logo and end plug
Seat Post	Jamis carbon fiber micro-adjust, 31.6 x 300mm with Jamis 7075-AL CNC aluminum 1-bolt seat post clamp
Saddle	Fizik Arione R7 with Intergrated Clip system and MG rails
Sizes	48, 51, 54, 56, 58, 61cm
Color	Inferno

UPGRADES/CHANGES FROM 2015

- Jamis Road Dyad Plus T700/FRP mono-coque carbon fiber frame
- Shimano Dura-Ace RD-9000 rear derailleur
- Fizik Arione R7 saddle
- Enduro Evo PressFit 30 BB

REASONS TO UPGRADE FROM XENITH COMP

- Shimano Ultegra 11-Speed group including crankset
- Dura-Ace RD-9000 rear derailleur
- Mavic Aksium Race 11-Speed wheelset with Vittoria Zaffiro Pro Slick tires
- Shimano BR-6010 direct mount rear brake

TOP 5 THINGS YOU NEED TO KNOW

Ultegra has long been recognized as a solid performer thanks to Shimano's Systems Engineering approach. Lighter, more stylish and advanced by the latest Dura-Ace technologies, Ultegra 11-speed is a beautifully balanced group with optimal performance and specifications.

fizik is a pure racing saddle brand 100% made in Italy. With the fizik Arione R7, featuring MG rails and the neat Integrated Clip system, you are ready for the podium.

Ultegra FC-6800 52/36 mid compact crankset and 11-28 cassette supplies a wide range of gear ratios to take on any terrain.

The Ritchey Comp Cockpit is tested to twice the EN standards providing you a confident steering & handling package.

The Aksium 11-speed wheelset provides you with top Mavic technologies. Straight-pull aerodynamic spokes, new lightweight rims and serviceable cartridge bearings.

GEOMETRY

SIZE	EFFECTIVE TT LENGTH	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
48	20.27 / 515	71.5°	73°	15.94 / 405	37.20 / 958	1.97 / 50	2.67 / 68	3.94 / 100	28.07 / 713	19.53 / 496	14.29 / 363
51	20.83 / 529	72°	73°	15.94 / 405	38.15 / 969	1.97 / 50	2.67 / 68	4.72 / 120	29.17 / 741	20.35 / 517	14.61 / 371
54	21.42 / 544	73°	73°	15.94 / 405	38.07 / 967	1.69 / 43	2.67 / 68	5.51 / 140	30.08 / 764	21.34 / 542	14.88 / 378
56	22.24 / 565	73°	73°	15.94 / 405	38.90 / 988	1.69 / 43	2.67 / 68	6.30 / 160	30.71 / 780	22.09 / 561	15.51 / 394
58	22.83 / 580	73°	73°	15.94 / 405	39.49 / 1003	1.69 / 43	2.67 / 68	7.09 / 180	31.38 / 797	22.83 / 580	15.83 / 402
61	23.23 / 590	73°	73°	15.94 / 405	39.92 / 1014	1.69 / 43	2.67 / 68	7.87 / 200	32.08 / 815	23.58 / 599	16.02 / 407