

# BOSS CRUISER 7-SPD

## SPECIFICATIONS

Frame	Diamond frame design with 6061 aluminum oversized tubing, sloping top tube design, water bottle bosses, alloy kickstand, and painted steel chainguard
Fork	Oversized hi-tensile steel tubular unicrown with leading dropout and fender boss
Headset	Sealed, 1 1/8"
Wheels	Alex Y303 36H black anodized alloy rims with alloy nuted hubs and 14 gauge stainless steel spokes
Tires	Jamis Cruise-control comfort tread, 26x2.125" with white stripe
Derailleurs	Shimano TX51 rear
Shiftlevers	Shimano Revoshift RS-35, 7-speed
Chain	KMC Z51NP, silver
Cassette	Shimano, 14-28, 7-Speed
Crankset	Forged alloy crank, 170mm alloy, with 44T compact disc chainring
BB Set	Cotterless bolt type, 3PB axle, 68 x 119mm
Pedals	Cruiser platform with TPE comfort insert
Brakeset	Tektro alloy linear pull brake with Tektro CL530 alloy levers
Handlebar	Jamis Cruise-control comfort bar
Stem	Alloy hi-rise, 180mm quill, 100mm extension, with removeable 2-bolt cap
Grips	Comfort style
Seat Post	Alloy micro-adjust, 27.2 x 300mm, with 31.8mm alloy clamp and crmo seatpin
Saddle	Boss Cruiser design with extra padding and heavy-duty, double-loop springs
Sizes	M: S (17"), M (19"), L (21"), XL (23") S/O: S (14"), M (18")
Color	M: Cosmo Blue, Gloss Black, Cayenne S/O: Cosmo Blue, Spearmint, Twilight
Weight	33.0 lbs



Cayenne



Gloss Black

Cosmo Blue

Spearmint

Twilight

Cosmo Blue

## UPGRADES/CHANGES FROM 2016

Same quality Jamis specification as 2016

## REASONS TO UPGRADE FROM BOSS CRUISER COASTER

Shimano 7-speed drivetrain

Shimano Revoshift twist-shifters

## GEOMETRY

SIZE	CENTER of BB to TOP of TT	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
S	16.02 / 407	22.32 / 567	69°	70°	18.74 / 476	42.28 / 1074	1.57 / 40	10.71 / 272	4.33 / 110	28.39 / 721
M	17.91 / 455	22.68 / 576	70°	70°	18.74 / 476	42.09 / 1069	1.57 / 40	10.71 / 272	4.92 / 125	29.80 / 757
L	20.00 / 508	23.39 / 594	70°	70°	18.74 / 476	42.83 / 1088	1.57 / 40	10.71 / 272	5.91 / 150	31.22 / 793
XL	22.01 / 559	23.39 / 594	70°	70°	18.74 / 476	42.83 / 1088	1.57 / 40	10.71 / 272	7.87 / 200	33.07 / 840
S/O	9.41 / 239	22.32 / 567	69°	70°	18.74 / 476	42.09 / 1069	1.57 / 40	10.71 / 272	4.33 / 110	24.21 / 615
M/O	9.41 / 239	22.68 / 576	70°	70°	18.74 / 476	42.09 / 1069	1.57 / 40	10.71 / 272	4.33 / 110	24.25 / 616