

CITIZEN 2

SPECIFICATIONS

Frame	6061 aluminum triple gauge main tubes with hydro-formed top tube, center-mount kickstand plate, replaceable derailleur hanger and fender/rack eyelets
Fork	RST Neon-T suspension fork, coil spring with external preload adjustment, 60mm travel
Headset	Water-resistant sealed mechanism, threaded, 1 1/8"
Wheels	Weinmann ZAC-19 double wall alloy rims, 32H, alloy hubs with QR and 14g stainless steel spokes
Tires	CST Marathon/Tour C-1446, silver safety stripe, 700x38c
Derailleurs	Shimano Altus RD-M310 rear and Shimano FD-TY710 front, 31.8mm clamp, top swing/dual pull front
Shiftlevers	Shimano Ez-Fire Plus, ST-EF510, 21-speed
Chain	KMC Z7
Cassette	Shimano MF-TZ31 7-speed, 14-34T
Crankset	Shimano FC-TY501, 48/38/28T, 170mm with chainguard
BB Set	FSA sealed cartridge, 68 x 122.5mm
Pedals	Comfort platform style with TPE non-slip insert
Brakeset	Promax TX-121 linear-pull with front power modulator and Shimano levers
Handlebar	Comfort hi-rise, steel, 25.4 x 80mm rise x 15° sweep x 640mm
Stem	Jamis alloy angle-adjustable, 90mm with 150mm quill (14-17"), 110mm with 180mm quill (18-23")
Grips	Anatomic triple density kraton
Seat Post	Suspension alloy micro-adjust, 27.2 x 350mm with alloy clamp and QR seatpin. 300mm for Men's 15, 17, Step-Thru 14
Saddle	Jamis Comfort with memory foam, synthetic suede cover, burnished sides and bumper springs with satin steel rails, gender specific
Accessories	Kickstand
Sizes	M: 15", 17", 19", 21", 23" S/T: 14", 18"
Color	M: Dakota Grey or Winter Blue S/T: Radiant Orchid or Pearl White
Weight	32.0 lbs



Winter Blue



Dakota Grey

UPGRADES/CHANGES FROM 2016

Shimano FC-TY501 crankset

REASONS TO UPGRADE FROM CITIZEN 1

Lightweight aluminum frame

RST Neon-T suspension fork, coil spring with external preload adjustment, 60mm travel

Weinmann lightweight 32H double wall rims

Jamis Comfort memory foam saddle

Suspension alloy micro-adjust seat post

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
15	21.50 / 546	70°	74°	17.52 / 445	41.69 / 1059	1.97 / 50	11.22 / 285	4.72 / 120	28.66 / 728
17	22.11 / 562	70°	74°	17.52 / 445	42.28 / 1074	1.97 / 50	11.22 / 285	4.72 / 120	29.05 / 738
19	22.48 / 571	71°	73.5°	17.52 / 445	42.05 / 1068	1.97 / 50	11.22 / 285	4.72 / 120	30.39 / 772
21	23.06 / 586	71°	73.5°	17.52 / 445	42.68 / 1084	1.97 / 50	11.22 / 285	5.12 / 130	31.65 / 804
23	23.46 / 596	71°	73.5°	17.52 / 445	43.07 / 1094	1.97 / 50	11.22 / 285	5.71 / 145	32.91 / 836
14 S/O	21.49 / 546	70°	74°	17.52 / 445	41.77 / 1061	1.97 / 50	11.22 / 285	5.90 / 150	18.62 / 473
18 S/O	21.88 / 556	70°	73.5°	17.52 / 445	41.97 / 1066	1.97 / 50	11.22 / 285	6.49 / 165	18.15 / 461