

EXPLORER 1

SPECIFICATIONS

Frame	Sport comfort design, hi-tensile steel with low-standover/upright ride position, center-mount kickstand bracket
Fork	Coil-spring suspension, alloy crown, chrome-plated stanchions, mini boots, 60mm travel
Headset	ATB sealed, threaded, 1 1/8"
Wheels	Alex C-1000 alloy rims, 36H, with Formula alloy hubs, QR front and rear, 14g stainless steel spokes
Tires	Jamis Sport Comfort, 26 x 1.95", blackwall
Derailleurs	SRAM X rear, Shimano M191 31.8mm top swing/dual pull front
Shiftlevers	SRAM 3.0 Comp ESP twist-shift, 21-speed
Chain	KMC UG51
Cassette	Shimano freewheel 7-speed, 14-34
Crankset	SR XCC alloy crank with 48/38/28 chainrings, 170mm crank length, with chainguard
BB Set	VP sealed bolt type, 3RB axle, 68 x 129mm (35-52-42)
Pedals	Comfort platform with TPE non-slip insert
Brakeset	ProMax alloy direct pull brakes with Tekro Tenera levers
Handlebar	Hi-rise comfort, 15D sweep x 80mm rise x 640mm wide
Stem	Jamis alloy, angle-adjustable, 90mm ext x 150mm quill (13.5-17.5") or 110mm ext x 180mm quill (18-21")
Grips	Kraton comfort
Seat Post	Suspension, alloy micro-adjust, 350mm x 25.4mm, with alloy QR clamp
Saddle	Jamis Comfort with extra thick padding, synthetic suede top, burnished side panels and bumper springs
Sizes	M: S (13"), M (15"), L (18"), XL (21") S/T: S (14"), M (17")
Color	M: Cayenne or Gloss Black S/T: Spearmint or Pure White
Weight	35.5 lbs



Cayenne



Gloss Black

UPGRADES/CHANGES FROM 2016

Same quality Jamis specification as 2016

GEOMETRY

SIZE	CENTER of BB to TOP of TT	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
S	11.30 / 287	21.06 / 535	68.39°	70.39°	16.73 / 425	40.12 / 1019	1.77 / 45	12.09 / 307	4.72 / 120	27.20 / 691
M	13.31 / 338	21.65 / 550	68.40°	70.40°	16.73 / 425	40.75 / 1035	1.77 / 45	12.09 / 307	5.51 / 140	28.78 / 731
L	15.79 / 401	22.64 / 575	68.42°	70.42°	16.73 / 425	41.77 / 1061	1.77 / 45	12.09 / 307	6.89 / 175	30.79 / 782
XL	18.78 / 477	23.43 / 595	68.44°	70.44°	16.73 / 425	42.60 / 1082	1.77 / 45	12.09 / 307	8.27 / 210	33.07 / 840
S/S/T	5.79 / 147	20.67 / 525	68.39°	70.39°	16.93 / 430	39.96 / 1015	1.77 / 45	12.09 / 307	6.30 / 160	17.87 / 454
M/S/T	7.05 / 179	22.05 / 560	68.39°	70.41°	16.93 / 430	41.42 / 1052	1.77 / 45	12.09 / 307	6.89 / 175	18.74 / 476