

EXPLORER 2

SPECIFICATIONS

Frame	6061 TIG-welded aluminum, all-new sport comfort design with low-standover/upright ride position, replaceable derailleur hanger, center-mount kickstand bracket
Fork	RST Capa-T coil-spring suspension with external preload, alloy crown, CP stanchions, mini-boots, 80mm travel
Headset	Internal cup, threaded, 1 1/8"
Wheels	Alex DC-25 double-wall alloy rims, 32H, KT Quando alloy hubs with QR, 14g stainless steel spokes
Tires	Jamis Sport Comfort, 26 x 1.95", with puncture-resistant casing
Derailleurs	Shimano Altus M310 rear, Shimano TY710 31.8mm top swing/dual pull front
Shiftlevers	Shimano RevoShift RS-45, 24-speed
Chain	KMC Z7
Cassette	Shimano HG20, 8-speed, 12-32
Crankset	Shimano TY701 alloy crank with 48/38/28 chainrings, 170mm crank length, with chainguard
BB Set	Sealed cartridge, 68 x 110.5mm
Pedals	Comfort platform with TPE non-slip insert
Brakeset	Tektro forged alloy direct pull brakes with Tektro CL530 alloy comfort levers
Handlebar	Hi-rise comfort, 15D sweep x 80mm rise x 640mm wide
Stem	Jamis alloy, angle-adjustable, 90mm ext x 150mm quill (13.5-17.5") or 110mm ext x 180mm quill (18-21")
Grips	Kraton comfort
Seat Post	Suspension, alloy micro-adjust, 350mm x 27.2mm, with alloy QR clamp
Saddle	Jamis Comfort with memory foam, synthetic suede top, burnished side panels and bumper springs
Sizes	M: S (13"), M (15"), L (18"), XL (21") S/T: S (14"), M (17")
Color	M: Radiant Blue or Silver Mist S/T: Silver Mist or Radiant Teal
Weight	32.5 lbs



Silver Mist



Radiant Blue

UPGRADES/CHANGES FROM 2016

Shimano FC-TY701 crankset

Shimano HG20, 8-speed cassette

Shimano RS45, 3x8 shifters

REASONS TO UPGRADE FROM EXPLORER 1

Lightweight aluminum frame

RST Capa-T suspension fork

Shimano 24-speed Revoshift twist-shifting drivetrain

Alex DC25 double-walled rims

Memory foam saddle

Sealed cartridge BB

GEOMETRY

SIZE	CENTER of BB to TOP of TT	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB HEIGHT	HEADTUBE	STANDOVER
S	11.30 / 287	21.06 / 535	68.39°	70.39°	16.73 / 425	40.00 / 1016	1.65 / 42	12.09 / 307	4.72 / 120	27.01 / 686
M	13.31 / 338	21.65 / 550	68.40°	70.40°	16.73 / 425	40.63 / 1032	1.65 / 42	12.09 / 307	5.51 / 140	28.62 / 727
L	15.79 / 401	22.64 / 575	68.42°	70.42°	16.73 / 425	41.65 / 1058	1.65 / 42	12.09 / 307	6.89 / 175	30.59 / 777
XL	18.78 / 477	23.43 / 595	68.44°	70.44°	16.73 / 425	42.48 / 1079	1.65 / 42	12.09 / 307	8.27 / 210	32.91 / 836
S/S/T	5.63 / 143	20.67 / 525	68.39°	70.39°	16.93 / 430	39.84 / 1012	1.65 / 42	12.09 / 307	6.30 / 160	17.83 / 453
M/S/T	7.05 / 179	22.05 / 560	68.39°	70.41°	16.93 / 430	41.26 / 1048	1.65 / 42	12.09 / 307	6.89 / 175	18.70 / 475