

NEMESIS PRO

SPECIFICATIONS

Frame	Mid Modulus Dyad Plus carbon fiber, 1.5 - 1 1/8" tapered head tube, PressFit30 BB shell, High Direct Mount (HDM) front derailleur with internal cable routing, post mount disc brakes & 12x142mm drop-out, stainless steel chain stay protector, replaceable derailleur hanger, Rock Shox maxle axle
Fork	Fox 32 Float Step Cast Performance Series 27.5" w/3-position compression & lock-out, 15x110mm axle, air spring compression, rebound adjust, tapered alloy steerer, 100mm travel
Headset	FSA Orbit 1.5 Zero-Stack internal bearing, 8mm cone spacer
Wheels	DT Swiss M1900 Spline 27.5" tubeless wheels, 15x110mm front, 12x142mm rear
Tires	Vittoria Peyote, 27.5 x 2.1", folding
Derailleurs	Shimano SLX Shadow Plus, 11-speed
Shiftlevers	Shimano SLX, 1x11-speed
Chain	KMC X11-1 EPT (Anti-Rust), 11-speed
Cassette	Shimano M7000, 11-speed, 11-42T
Crankset	Shimano SLX, 32T, 170mm (15"), 175mm (17-21")
BB Set	Shimano External
Pedals	N/A
Brakeset	Shimano SLX hydraulic disc, 160mm front & rear RT70 centerlock rotors
Handlebar	Ritchey Trail, 710mm x 20mm rise
Stem	Ritchey Trail, 80mm (15"), 90mm (17"), 100mm (19"), 110mm (21")
Grips	Jamis Lock-On
Seat Post	Ritchey Trail Comp, 31.6 x 400mm
Saddle	WTB Volt Comp
Sizes	15", 17", 19", 21"
Color	Carbon
Weight	21.75 lbs



TECH FEATURES

nearnet
MOLDING

Equipped with
Enduro
PRESS FIT 30BB

UPGRADES/CHANGES FROM 2016

Fox 32 Step Cast Performance Series fork

DT Swiss M1900 Spline tubeless wheelset

Shimano SLX 1x11 drivetrain & brakes

Ritchey Trail cockpit

REASONS TO UPGRADE FROM NEMESIS RACE

Fox Performance Series fork

DT Swiss M1900 Spline wheelset

Shimano SLX 1x11 drivetrain & brakes

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
15	22.1 / 560	70°	72.5°	17.1 / 435	41.1 / 1045	1.7 / 42.5	3.9 / 100	29.5 / 750	22.9 / 582	14.6 / 371
17	23.0 / 585	70°	72.5°	17.1 / 435	42.1 / 1070	1.7 / 42.5	4.3 / 110	30.9 / 785	23.3 / 591	15.5 / 393
19	23.8 / 605	70°	72.5°	17.1 / 435	43.0 / 1091	1.7 / 42.5	5.1 / 130	31.4 / 797	24.0 / 610	16.0 / 407
21	24.6 / 625	70°	72.5°	17.1 / 435	43.8 / 1112	1.7 / 42.5	5.5 / 140	32.1 / 815	24.4 / 619	16.7 / 424