

QUEST SPORT

SPECIFICATIONS

Frame	4130 double-buttet chromoly main tubes with SSD frame geometry and SST tubing diameters, sloping top tube frame design, double-tapered cromoly stays, forged dropouts and fender/rack eyelets
Fork	Full 4130 chromoly lugged crown, radius blades, forged dropouts with fender eyelets
Headset	Ritchey LB threadless, 1 1/8"
Wheels	Alex AT 470 rim with TCS (Tubeless Compatible System) with CNC sidewalls, 28/32H, Formula alloy hubs with QR and 14g stainless steel spokes
Tires	Vittoria Zaffiro, 700 x 25c
Derailleurs	Shimano Claris RD-2400 GS rear and Shimano Claris FD-2403 front with 28.6mm alloy clamp
Shiftlevers	Shimano Claris ST-2400 Dual Control STI, 24-speed
Chain	KMC Z8
Cassette	Shimano HG41 8-speed, 11-32T
Crankset	Shimano Claris FC-2403, 52/42/30T, 170mm (48/5154), 175mm (56/58/61)
BB Set	FSA sealed cartridge, 68 x 116mm
Pedals	Touring platform style, full alloy with toe clips
Brakeset	Tektro R317 long reach dual-pivot calipers with adjustable pads Shimano Claris ST-2400 STI levers
Handlebar	Jamis Ergo, 6061 aluminum, 31.8 x 380mm (48), 400mm (51/54), 420mm (56/58/61)
Stem	Jamis Road, 3D forged 6061 alloy, 7" x 90mm (48/51), 100mm (54/56), 110mm (58/61)
Grips	Jamis suede tape
Seat Post	Jamis alloy micro-adjust, 26.6 x 300mm with cromoly seat pin
Saddle	Jamis Touring Sport with pressure relief cut-out
Sizes	48, 51, 54, 56, 58, 61cm
Color	Gloss Black or Cosmo Blue
Weight	25.0 lbs



Cosmo Blue

TECH FEATURES



UPGRADES/CHANGES FROM 2016

- Redesigned SSD frame geometry
- Alex AT 470 rims with TCS (Tubeless Compatible System)
- Shimano HG41 8-speed, 11-32T cassette



Gloss Black

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
48	20.24 / 514	71°	75°	16.34 / 415	39.09 / 993	1.97 / 50	2.79 / 71	5.24 / 133	29.01 / 737	21.53 / 547	14.44 / 367
51	21.02 / 534	72°	74°	16.34 / 415	39.13 / 994	1.97 / 50	2.74 / 69.5	5.94 / 151	30.24 / 768	22.30 / 566	14.61 / 371
54	21.85 / 555	72.5°	73°	16.54 / 420	39.33 / 999	1.69 / 43	2.68 / 68	6.61 / 168	30.98 / 787	23.07 / 586	14.79 / 376
56	22.24 / 565	73°	73°	16.54 / 420	39.53 / 1004	1.69 / 43	2.68 / 68	7.32 / 186	31.77 / 807	23.81 / 605	14.96 / 380
58	22.60 / 574	73°	73°	16.73 / 425	40.08 / 1018	1.69 / 43	2.62 / 66.5	8.15 / 207	32.48 / 825	24.55 / 624	15.09 / 383
61	22.99 / 584	73°	73°	16.73 / 425	40.47 / 1028	1.69 / 43	2.62 / 66.5	8.94 / 227	33.23 / 844	25.39 / 645	15.26 / 388