

ALLEGRO COMP FEMME

SPECIFICATIONS

Frame	Size Specific Design Triple-butted 6061 aluminum with internal cable routing, hydro-formed top and down tube, taper gauge "S" bend stays with disc brake post mounts, replaceable derailleur hanger and fender/rack eyelets
Fork	Aluminum air-formed fork with disc brake mounts, aluminum steerer, low-rider carrier mounts, forged dropouts and fender eyelets
Headset	FSA Integrated IS threadless with nylon upper compression ring, 1 1/8"
Wheels	Alex TD26 double wall disc specific alloy rims, 32H, Formula 6-bolt alloy hubs with QR and 14g stainless steel spokes
Tires	Vittoria Randonneur with Double Shield puncture protection and reflective sidewalls, 700 x 32c
Derailleurs	Shimano Acera RD-M360 rear and Shimano FD-M310 front
Shiftlevers	Shimano Rapidfire SL-M310, 24-speed
Chain	KMC Z7
Cassette	Shimano HG41 8-speed, 11-32T
Crankset	Shimano FC-TY501, 48/38/28, 170mm (14-18")
BB Set	FSA sealed cartridge, 68 x 110.5mm
Pedals	Platform style, steel cage/resin body
Brakeset	Tektro Novela mechanical disc brakes with 160mm rotors and Tektro brake levers
Handlebar	Jamis Flat bar, 6061 T-6 aluminum, 31.8 x 10" sweep x 580mm
Stem	Jamis adjustable threadless system (ATS), forged aluminum, 10" x 90mm (14-18"). ATS shim length 100mm
Grips	Anatomic double density kraton
Seat Post	Jamis alloy micro-adjust, 27.2 x 350mm alloy clamp with QR seatpin
Saddle	Jamis Touring Femme with SL cover
Sizes	14", 16", 18"
Color	Pure White
Weight	25.5 lbs



TECH FEATURES



Femme

UPGRADES/CHANGES FROM PREVIOUS MODEL

Same Quality Jamis specification as previous model

REASONS TO UPGRADE FROM ALLEGRO SPORT

Disc brake frame and fork

Aluminum fork

Shimano Acera RD-M360 rear and Shimano FD-M310 front derailleur

Alex TD-26 disc specific rims

Tektro Novela mechanical disc brakes with 160mm rotors

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
14	20.47 / 520	70.5°	74.5°	17.13 / 435	40.31 / 1024	1.97 / 50	2.16 / 55	4.92 / 125	28.38 / 721	20.98 / 533	14.57 / 370
16	20.86 / 530	71°	74°	17.13 / 435	40.35 / 1025	1.97 / 50	2.16 / 55	5.31 / 135	28.86 / 733	21.46 / 545	14.64 / 372
18	21.26 / 540	71°	74°	17.13 / 435	40.79 / 1036	1.97 / 50	2.16 / 55	5.90 / 150	29.92 / 760	22.01 / 559	14.88 / 378