

CITIZEN 3

SPECIFICATIONS

Frame	6061 aluminum triple gauge main tubes with hydro-formed top tube, sloping design for men's, step through design for ladies, center-mount kickstand plate, replaceable derailleur hanger and fender/rack eyelets
Fork	SR/Suntour NEX HLO suspension, coil spring with preload adjuster and hydraulic lockout, 63mm travel
Headset	Water-resistant sealed mechanism, threaded, 1 1/8"
Wheels	Alex ID-19 double wall alloy rims with GSW sidewall, 32H, Formula alloy hubs with QR and 14g stainless steel spokes
Tires	CST Marathon/Tour C-1446 with silver safety stripe, 700 x 38c
Derailleurs	Shimano Acera RD-M360 rear and Shimano FD-TY710 front, 31.8mm, top swing/dual pull front.
Shiftlevers	Shimano Altus Rapid Fire SL-M310, 24-speed
Chain	KMC Z7
Cassette	SRAM 8-speed, 11-32T
Crankset	Shimano FC-TY701, 48/38/28T, 170mm with chainguard
BB Set	VP sealed cartridge, 68 x 122.5mm
Pedals	Comfort platform style with TPE non-slip insert
Brakeset	Tektro 855AL forged alloy linear-pull brakes with front power modulator and Tektro CL530 ergonomic designed alloy levers with kraton insert
Handlebar	Comfort hi-rise, alloy 25.4 x 80mm rise x 15" sweep x 640mm
Stem	Jamis alloy angle-adjustable, 90mm with 150mm quill (14-17"), 110mm with 180mm quill (18-23")
Grips	Anatomic triple density kraton
Seat Post	Suspension alloy micro-adjust, 27.2 x 350mm with alloy clamp and QR seatpin. 300mm for Men's 15, 17, Step-Thru 14
Saddle	Jamis Comfort with Memory Foam, synthetic suede cover, burnished sides and bumper springs with satin steel rails, gender specific
Accessories	Kickstand
Sizes	M: 15", 17", 19", 21", 23" S/T: 14", 18"
Color	M: Ink S/T: Ink or Pomegranate
Weight	32.75 lbs



UPGRADES/CHANGES FROM PREVIOUS MODEL

SR/Suntour NEX HLO suspension fork 63mm travel

Jamis lightweight aluminum bar

REASONS TO UPGRADE FROM CITIZEN 2

SR/Suntour NEX HLO suspension fork 63mm travel

Shimano FC-TY701 crankset

Shimano 24-speed Altus Rapid Fire SL-M310 shifter/brake levers & Acera M360 rear derailleur

Sram 8-speed cassette

Tektro forged alloy linear-pull brakeset and lever

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER
15	21.42 / 544	70°	74°	17.52 / 445	41.69 / 1059	1.97 / 50	2.56 / 65	4.72 / 120	28.46 / 723
17	22.05 / 560	70°	74°	17.52 / 445	42.28 / 1074	1.97 / 50	2.56 / 65	4.72 / 120	29.57 / 751
19	22.40 / 569	71°	73.5°	17.52 / 445	42.05 / 1068	1.97 / 50	2.56 / 65	4.72 / 120	30.83 / 783
21	22.99 / 584	71°	73.5°	17.52 / 445	42.68 / 1084	1.97 / 50	2.56 / 65	5.12 / 130	32.16 / 817
23	23.38 / 594	71°	73.5°	17.52 / 445	43.07 / 1094	1.97 / 50	2.56 / 65	5.71 / 145	33.23 / 844
14 S/T	21.42 / 544	70°	74°	17.52 / 445	41.77 / 1061	1.97 / 50	2.56 / 65	5.90 / 150	18.50 / 470
18 S/T	21.81 / 554	70°	73.5°	17.52 / 445	41.97 / 1066	1.97 / 50	2.56 / 65	6.49 / 165	18.11 / 460