

COMMUTER 3

SPECIFICATIONS

Frame	6061 triple gauge aluminum main tubes and stays, new sloping design, kickstand mount, forged dropouts and fender/rack eyelets
Fork	Jamis City/Cross alloy unicrown, straight blades, forged dropouts with low rider mounts and double fender eyelets
Headset	Water-resistant sealed mechanism, threaded 11/8"
Wheels	Alex ID-19 double wall alloy rims, 32H, alloy hubs with QR and 14g stainless steel spokes
Tires	CST Corporal with puncture protection and silver safety stripe, 700 x 32c
Derailleurs	Shimano Claris RD-R2000 GS rear and Shimano Claris FD-R2000 front with 31.8mm alloy clamp
Shiftlevers	Shimano Claris SL-R2000, 16-speed
Chain	KMC Z7
Cassette	Shimano HG31, 8-speed, 11-32T
Crankset	Forged alloy crank, 48/36, 170mm (14-18"), 175mm (19-23"), with outter guard
BB Set	FSA sealed cartridge, 68 x 122.5mm
Pedals	Comfort platform with TPE non-slip insert
Brakeset	Tektro HD-M285 post mount hydraulic disc brakes with 160mm 6-bolt rotors and Tektro levers
Handlebar	Jamis ARC, 6061 aluminum, 25.4 x 35° sweep x 580mm (F 14", 18") 600mm (M 15", 17", 19", 21", 23")
Stem	Jamis alloy hi-rise, quill type, 35° x 90mm with 180mm quill
Grips	Anatomic double density kraton with reflective end plug
Seat Post	Jamis alloy micro-adjust, 27.2 x 350mm with alloy clamp and QR seatpin
Saddle	Jamis Metro Sport with memory foam, synthetic leather cover, burnished sides, gender specific
Accessories	



TECH FEATURES

UPGRADES/CHANGES FROM PREVIOUS MODEL

REASONS TO UPGRADE FROM COMMUTER 2

Aluminum disc brake frame and fork

CST Corporal with puncture protection and silver safety stripe

Shimano Claris 16-speed group

Forged 48/36 alloy crank

Tektro HD-M285 hydraulic disc brakes with Tektro lever

Aluminum disc brake frame and fork

Shimano Claris 16-speed group

Forged 48/36 alloy crank

Tektro HD-M285 hydraulic disc brakes with Tektro lever

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
15	21.53 / 547	70°	73.5°	17.52 / 445	41.5 / 1053	1.97 / 50	2.75 / 70	4.92 / 125	27.64 / 702	22.62 / 574.7	14.83 / 376.8
17	22.12 / 562	70.5°	73.5°	17.52 / 445	41.9 / 1064	1.97 / 50	2.75 / 70	5.71 / 145	29.13 / 740	23.45 / 595.6	15.18 / 385.6
19	22.48 / 571	71°	73.5°	17.52 / 445	42.1 / 1069	1.97 / 50	2.75 / 70	6.30 / 160	30.47 / 774	24.09 / 611.9	15.35 / 389.9
21	23.03 / 585	71°	73°	17.52 / 445	42.2 / 1072	1.97 / 50	2.75 / 70	7.28 / 185	31.93 / 811	25.11 / 637.7	15.35 / 390.0
23	23.42 / 595	71.5°	73°	17.52 / 445	42.6 / 1083	1.97 / 50	2.75 / 70	8.66 / 220	33.38 / 848	26.41 / 670.9	15.35 / 389.9
14 S/O	21.50 / 546	70°	74.5°	17.52 / 445	41.9 / 1063	1.97 / 50	2.75 / 70	4.72 / 120	25.24 / 641	22.44 / 570	15.27 / 387.9
18 S/O	21.89 / 556	71°	74°	17.52 / 445	41.7 / 1058	1.97 / 50	2.75 / 70	5.12 / 130	25.87 / 657	22.97 / 583.5	15.30 / 388.7