

DAKAR A1

SPECIFICATIONS

Frame	Triple-buttet 6061 alloy, 120mm travel mp2 suspension, 1.5 - 1 1/8" tapered head tube, asymmetrical chainstays w/12x142mm thru-axle dropouts, internal dropper post routing, ISCG05 chainguide mount, Rock Shox Monarch RL Debon air shock with rebound adjust & lockout, replaceable derailleur hanger, Formula thru-axle
Fork	Rock Shox Recon RL 27.5", Solo Air spring compression, tapered steerer, lever actuated lockout, external rebound, 32mm stanchions, magnesium lowers, 15x100mm axle, 120mm travel
Headset	FSA Orbit 1.5 Zero-Stack internal cup, 8mm cone spacer
Wheels	WTB ST i23 TCS 27.5" tubeless rims, 32H, Formula sealed bearing 15x100mm front & 12x142mm rear 6-bolt disc hubs, stainless spokes
Tires	Vittoria Goma, 27.5 x 2.25", folding
Derailleurs	SRAM GX, 11-speed
Shiftlevers	SRAM NX, 1x11-speed
Chain	KMC X11-1, 11-speed
Cassette	SRAM 1130, 11-speed, 11-42T
Crankset	Race Face Aeffect, 32T, 170mm (XS/S), 175mm (M-XL)
BB Set	Race Face External
Pedals	N/A
Brakeset	Shimano M396 hydraulic disc, 180mm front & 160mm rear RT26 6-bolt rotors
Handlebar	Race Face Ride, 35 x 760mm
Stem	Race Face Ride, 50mm
Grips	Jamis Lock-On
Seat Post	KS eTen Integra, 100mm travel, Southpaw remote
Saddle	WTB Volt Sport
Sizes	XS (14.5), S (15.5), M (17), L (19), XL (21)
Color	Kinetic Grey
Weight	N/A



UPGRADES/CHANGES FROM DAKAR XC

- Revised frame design with 120mm travel
- Rock Shox Recon RL Air fork
- 11-speed drivetrain
- Race Face crankset & cockpit
- KS dropper seatpost
- Thru-axle hubs

REASONS TO UPGRADE FROM DAKAR A2

- 11-speed drivetrain w/Race Face Aeffect crankset
- KS eTen dropper seatpost
- 15mm axle front hub
- Shimano M396 brakes

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER
XS / 14.5	21.4 / 545	68°	75°	17.3 / 440	43.3 / 1100	0.71 / 18	3.9 / 100	28.7 / 728
S / 15.5	22.4 / 570	68°	75°	17.3 / 440	44.3 / 1125	0.71 / 18	3.9 / 100	29.2 / 742
M / 17	23.4 / 595	68°	75°	17.3 / 440	45.3 / 1150	0.71 / 18	4.3 / 110	29.8 / 757
L / 19	24.4 / 620	68°	75°	17.3 / 440	46.3 / 1175	0.71 / 18	4.7 / 120	29.7 / 753
XL / 21	25.4 / 645	68°	75°	17.3 / 440	47.2 / 1200	0.71 / 18	5.1 / 130	29.8 / 758