

DXT COMP

SPECIFICATIONS

Frame	Triple-butted 6061 aluminum with hydro-formed top and down tube, 1 1/8" head tube, new designed taper gauge "S" bend stays, seat stays and disc brake mounts, 34.9mm seat tube, replaceable derailleur hanger and fender/rack eyelets
Fork	SR/Suntour SF15-NVX HLO, aluminum lowers, coil spring, 28mm stanchions, 1-1/8" steerer, aluminum crown, hydraulic lock out, 75mm travel
Headset	Internal cup, threadless 1 1/8"
Wheels	Alex TD26 disc specific double wall alloy rims, 32H, Formula disc hubs and 14g stainless steel spokes
Tires	Ritchey Comp Speedmax Cross, 700 x 40c
Derailleurs	Shimano Altus RD-M2000 SGS rear and Altus FD-M370 top swing front
Shiftlevers	Shimano RapidFire SL-M2000, 24-speed
Chain	KMC Z99
Cassette	Shimano HG201 9-speed, 11-32T
Crankset	Shimano FC-M371, 48/36/26T, 170mm (15-17"), 175mm (19-23")
BB Set	FSA sealed cartridge, 68 x 110.5mm
Pedals	Full alloy platform, toe clip attachable
Brakeset	Tektro HD-M285 post mount hydraulic disc brakes with 160mm 6-bolt rotors and Tektro levers
Handlebar	Jamis Riser bar, 6061 double-butted aluminum, 31.8 x 20mm rise x 10° sweep x 600mm
Stem	Jamis Trekking, 3D forged alloy, 35° rise, 80mm (15-17"), 100mm (19/21/23")
Grips	Anatomic double density kraton grip with gel
Seat Post	Jamis alloy micro-adjust, 31.6 x 350mm alloy clamp with QR seatpin
Saddle	Selle Royal Seta M1 with integrated clip system
Sizes	15", 17", 19", 21", 23"
Color	Ano Black
Weight	29.75 lbs



TECH FEATURES



UPGRADES/CHANGES FROM PREVIOUS MODEL

Shimano Altus 9-speed group
Shimano FC-M371 crankset
Shimano RapidFire SL-M2000 shifters and Tektro Levers
Alex TD26 alloy double wall rims
KMC Z99 chain
Shimano HG201 9-speed, 11-32T cassette

REASONS TO UPGRADE FROM DXT SPORT

Shimano Altus 9-speed group
Shimano RapidFire SL-M2000 shifters and Tektro Levers
Shimano FC-M371 crankset
Tektro HD-M285 hydraulic disc brakes
Ritchey Comp Speedmax Cross, 700 x 40c
Selle Royal Seta M1 saddle

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
15	23.03 / 585	71°	73°	17.52 / 445	42.16 / 1071	1.65 / 42	2.36 / 60	4.13 / 105	28.94 / 735	22.68 / 576	16.06 / 408
17	23.62 / 600	71°	73°	17.52 / 445	42.75 / 1086	1.65 / 42	2.36 / 60	4.72 / 120	30.24 / 768	23.23 / 590	16.46 / 418
19	24.01 / 610	71°	73°	17.52 / 445	43.19 / 1097	1.65 / 42	2.36 / 60	5.31 / 135	31.34 / 796	23.78 / 604	16.69 / 424
21	24.61 / 625	71°	73°	17.52 / 445	43.78 / 1112	1.65 / 42	2.36 / 60	6.10 / 155	32.68 / 830	24.53 / 623	17.05 / 433
23	24.80 / 630	71°	73°	17.52 / 445	44.01 / 1118	1.65 / 42	2.36 / 60	6.89 / 175	34.05 / 865	21.34 / 542	17.01 / 432