

KOMODO

27.5+/29 SPORT

SPECIFICATIONS

Frame	Triple-buttet 6061 aluminum, 1.5 - 1 1/8" tapered head tube, post mount disc brakes, 12x148mm thru-axle drop-outs, High Direct Mount (HDM) front derailleur with front-pull internal cable routing, internal dropper post routing, replaceable derailleur hanger, Formula thru-axle
Fork	SR Suntour XCR 34 LOR 29/27.5+, coil spring, external rebound, lockout adjust, 34mm stanchions, tapered aluminum steerer, 15x110mm axle, 120mm travel
Headset	FSA Orbit 1.5 Zero-Stack internal cup, 8mm cone spacer
Wheels	WTB Scraper i40 TCS tubeless 27.5" rims, Formula 15x110mm front & 12x148mm rear sealed bearing 6-bolt disc hubs, stainless spokes
Tires	Vittoria Cannoli, 27.5 x 3.0"
Derailleurs	Shimano Deore Shadow Plus rear
Shiftlevers	Shimano Deore, 1x10-speed
Chain	KMC X10-1, 10-speed
Cassette	Shimano HG500, 10-speed, 11-42T
Crankset	SR Suntour Zeron, 32T, 170mm (15"), 175mm (17-21")
BB Set	SR Suntour External
Pedals	MTB alloy platform
Brakeset	Tektro M285 hydraulic disc, 180mm front & 160mm rear 6-bolt rotors
Handlebar	Race Face Ride, 710mm x 25mm rise
Stem	Race Face Ride, 60mm (15"), 70mm (17"), 80mm (19"), 90mm (21")
Grips	Dual compound
Seat Post	Race Face Ride, 31.6 x 400mm
Saddle	WTB Volt Sport
Sizes	15", 17", 19", 21"
Color	Ink
Weight	31.5 lbs



TECH FEATURES



CHANGES/UPGRADES FROM PREVIOUS MODEL

SR Suntour XCR 34 fork
 Shimano 1x10 drivetrain w/11-42T
 SR Suntour Zeron 1x crankset
 Vittoria Cannoli tires
 Race Face handlebar, stem & seatpost

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
15	22.8 / 580	68°	73°	17.1 / 435	43.6 / 1108	1.9 / 47	3.5 / 90	30.0 / 763	24.4 / 621	15.5 / 395
17	23.6 / 600	68°	73°	17.1 / 435	44.5 / 1130	1.9 / 47	4.3 / 110	31.1 / 790	24.6 / 626	16.1 / 410
19	24.4 / 620	68°	73°	17.1 / 435	45.3 / 1151	1.9 / 47	4.7 / 120	32.5 / 825	25.0 / 635	16.8 / 427
21	25.2 / 640	68°	73.5°	17.1 / 435	46.4 / 1179	1.9 / 47	5.5 / 140	33.9 / 861	25.7 / 653	17.6 / 448