

QUEST COMP FEMME

SPECIFICATIONS

Frame	Size Specific Design Reynolds 520 double-butted chromoly main tubes with SSD frame geometry and SST tubing diameters, sloping top tube frame design, double-tapered cromos stays, forged dropouts and fender/rack eyelets
Fork	Jamis Road ECO full carbon composite with carbon steerer, carbon drop out with stainless steel tabs with fender eyelets
Headset	Ritchey LB threadless, 1 1/8"
Wheels	Alex AT 470 rims with TCS (Tubeless Compatible System), 28/32H, Formula alloy hubs with QR and 14g stainless steel spokes
Tires	Vittoria Zaffiro, 700 x 28c
Derailleurs	Shimano Sora RD-R3000GS rear and Sora FD-R3030 front with 28.6mm alloy clamp
Shiftlevers	Shimano Sora ST-R3030 Dual Control STI, 27-speed
Chain	KMC Z99
Cassette	Shimano HG201 9-speed, 11-32T
Crankset	FSA Vero, 50/39/30T, 165mm (48), 170mm (51/54)
BB Set	FSA sealed cartridge, 68 x 116mm
Pedals	Touring platform style, full alloy with toe clips
Brakeset	Tektro R317 long reach dual-pivot calipers with adjustable pads and Shimano Sora ST-3500 STI levers
Handlebar	Ritchey Comp Logic Curve, 6061 aluminum, 31.8 x 380mm (48), 400mm (51/54)
Stem	Jamis adjustable threadless system (ATS), forged aluminum, 10" x 90mm (48/51), 105mm (54), ATS shim length 80mm
Grips	Jamis suede tape with gel
Seat Post	Jamis alloy micro-adjust, 27.2 x 300mm with cromos seat pin
Saddle	Selle Royal Seta S1 femme with integrated clip system
Sizes	48, 51, 54
Color	Sage
Weight	22.75 lbs



TECH FEATURES

REYNOLDS



ATS Adjustable Threadless System

Femme

ECO

UPGRADES/CHANGES FROM PREVIOUS MODEL

Jamis Road ECO full carbon fork

Vittoria Zaffiro, 700 x 28c

Jamis suede bar tape with gel

REASONS TO UPGRADE FROM QUEST SPORT

Reynolds 520 chromoly frame tubing

Jamis Road ECO full carbon fork

Shimano Sora R3000 27-speed group

FSA Vero 50/39/30T crankset

Ritchey Comp Logic Curve bar and Ritchey seat post

Jamis adjustable threadless system (ATS) stem

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
48	19.88 / 505	71°	75.5°	16.34 / 415	38.94 / 989	1.97 / 50	2.79 / 71	4.72 / 120	28.54 / 725	21.25 / 540	14.38 / 365
51	20.27 / 515	71.5°	75°	16.34 / 415	39.21 / 996	1.97 / 50	2.74 / 69.5	5.63 / 143	29.92 / 760	22.05 / 560	14.56 / 370
54	20.86 / 530	71.5°	74°	16.34 / 415	39.37 / 1000	1.69 / 43	2.74 / 69.5	6.38 / 162	30.67 / 779	22.85 / 580	14.75 / 375