

QUEST SPORT

SPECIFICATIONS

Frame	4130 double-buttet chromoly main tubes with SSD frame geometry and SST tubing diameters, sloping top tube frame design, double-tapered cromoly stays, forged dropouts and fender/rack eyelets
Fork	Full 4130 chromoly lugged crown, radius blades, forged dropouts with fender eyelets
Headset	Ritchey LB threadless, 1 1/8"
Wheels	Alex AT 470 rim with TCS (Tubeless Compatible System) with CNC sidewalls, 28/32H, Formula alloy hubs with QR and 14g stainless steel spokes
Tires	Vittoria Zaffiro, 700 x 25c
Derailleurs	Shimano Claris RD-2400 GS rear and Shimano Claris FD-2403 front with 28.6mm alloy clamp
Shiftlevers	Shimano Claris ST-2400 Dual Control STI, 24-speed
Chain	KMC Z8
Cassette	Shimano HG41 8-speed, 11-32T
Crankset	Shimano Claris FC-2403, 52/42/30T, 170mm (48/5154), 175mm (56/58/61)
BB Set	FSA sealed cartridge, 68 x 116mm
Pedals	Touring platform style, full alloy with toe clips
Brakeset	Tektro R317 long reach dual-pivot calipers with adjustable pads Shimano Claris ST-2400 STI levers
Handlebar	Jamis Ergo, 6061 aluminum, 31.8 x 380mm (48), 400mm (51/54), 420mm (56/58/61)
Stem	Jamis Road, 3D forged 6061 alloy, 7" x 90mm (48/51), 100mm (54/56), 110mm (58/61)
Grips	Jamis suede tape
Seat Post	Jamis alloy micro-adjust, 26.6 x 300mm with cromoly seat pin
Saddle	Jamis Touring Sport with pressure relief cut-out
Sizes	48, 51, 54, 56, 58, 61cm
Color	Black Coal or Silver Mist
Weight	25.0 lbs



Black Coal

TECH FEATURES



UPGRADES/CHANGES FROM PREVIOUS MODEL

Same Quality Jamis specification as previous model



Silver Mist

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
48	20.24 / 514	71°	75°	16.34 / 415	39.09 / 993	1.97 / 50	2.79 / 71	5.24 / 133	28.74 / 730	21.66 / 550	14.43 / 367
51	20.86 / 530	72°	74°	16.34 / 415	39.17 / 995	1.97 / 50	2.74 / 69.5	5.94 / 151	29.29 / 744	22.42 / 570	14.59 / 371
54	21.25 / 540	72.5°	73°	16.34 / 415	39.33 / 999	1.69 / 43	2.68 / 68	6.61 / 168	30.83 / 783	23.16 / 588	14.77 / 375
56	21.85 / 555	73°	73°	16.34 / 415	39.53 / 1004	1.69 / 43	2.68 / 68	7.32 / 186	31.61 / 803	23.90 / 607	14.94 / 379
58	22.44 / 570	73°	73°	16.34 / 415	40.08 / 1018	1.69 / 43	2.62 / 66.5	8.15 / 207	32.36 / 822	25.70 / 626	15.07 / 383
61	23.03 / 585	73°	73°	16.34 / 415	40.47 / 1028	1.69 / 43	2.62 / 66.5	8.94 / 227	33.11 / 841	25.39 / 645	15.23 / 387