

TRAIL X

SPECIFICATIONS

Frame	6061 aluminum main tubes, over-sized seat tube, zero-stack head tube, over-sized stays, replaceable derailleur hanger
Fork	SR Suntour XCT 27.5", coil spring, external preload adjuster, 28mm stanchions, aluminum lowers, 100mm travel 15"-21", 80mm travel 13"
Headset	Zero-stack internal cup threadless, 15mm cone spacer
Wheels	Alex TD26 27.5" rims, 32H, alloy 6-bolt disc hubs, 14G nickel-plated spokes
Tires	CST Patrol, 27.5 x 2.25"
Derailleurs	Shimano TY300 rear and TY500 front
Shiftlevers	Shimano EF41, 3x7-speed
Chain	KMC Z51, 7-speed
Cassette	Shimano TZ31, 7-speed, 14-34T
Crankset	Forged alloy crank, 42/34/24T, 170mm (15") 175mm (17"-21")
BB Set	Sealed cartridge
Pedals	MTB platform, hi-impact resin
Brakeset	Tektro M280 mechanical disc, 160mm rotors and Shimano levers
Handlebar	Jamis XC alloy riser, 31.8 x 20mm rise x 680mm
Stem	Jamis XC alloy threadless, 31.8 x 10° rise x 70mm (15"/17"), 90mm (19"/21")
Grips	Kraton
Seat Post	Jamis alloy micro-adjust, 31.6 x 350mm (15") 400mm (17"-21")
Saddle	Jamis ATB Sport, SL cover, protective front and rear guards
Sizes	13", 15", 17", 19", 21"
Color	Ano Black or Ano Palladium
Weight	32.75 lbs



Ano Palladium

UPGRADES/CHANGES FROM PREVIOUS MODEL

- SR Suntour XCT fork
- Tektro M280 mechanical disc brakeset
- Alex disc specific rims
- Oversized 31.8 handlebar & stem

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER
13"	21.1 / 535	70°	72.5°	17.1 / 435	40.3 / 1024	1.8 / 46	3.7 / 95	27.3 / 693
15"	22.0 / 559	70°	72.5°	17.1 / 435	41.3 / 1048	1.8 / 46	3.9 / 100	28.7 / 730
17"	23.3 / 585	70°	72.5°	17.1 / 435	42.3 / 1075	1.8 / 46	4.3 / 110	30.2 / 766
19"	23.8 / 605	70°	72.5°	17.1 / 435	43.1 / 1095	1.8 / 46	5.1 / 130	31.4 / 798
21"	24.6 / 625	70°	72.5°	17.1 / 435	43.9 / 1116	1.8 / 46	5.5 / 140	32.7 / 831



Ano Black