

VENTURA COMP

SPECIFICATIONS

Frame	Double-buttet 6061 aluminum, compact sloping top tube frame design with SSD frame geometry and SST tubing diameters, 11.5 - 1 1/8" tapered head tube, butted seat tube for 27.2 seat post, flat mount disc brake mount, replaceable derailleur hanger and fender/rack eyelets
Fork	Jamis Performance ECO carbon composite, 1.5" hollow formed crown, monocoque one-piece forming technology, alloy dropouts, flat mount disc brake mount with internal cablerouting, exposed fender eyelets
Headset	FSA Integrated, threadless, 1.5 - 1 1/8"
Wheels	Alex ATD 470 disc specific rims with TCS (Tubeless Compatible System), 32H, Formula 6-bolt alloy hubs with QR and 14g stainless steel spokes
Tires	Vittoria Zaffiro, 700 x 25c
Derailleurs	Shimano Sora RD-R3000 rear and Sora FD-R3000 front with 31.8mm alloy clamp
Shiftlevers	Shimano Sora ST-R3000 Dual Control STI, 18-speed
Chain	KMC Z99
Cassette	Shimano HG200 9-speed, 11-32T
Crankset	FSA Vero, 50/34T, 170mm (48/51), 172.5mm (54/56), 175mm (58/61)
BB Set	FSA sealed cartridge, 68 x 110.5mm
Pedals	Touring platform style, full alloy with toe clips
Brakeset	Tektro Lyra mechanical disc brakes and Shimano Sora ST-R3000 STI levers
Handlebar	Ritchey Logic, 6061 aluminum, 31.8 x 400mm (48/51) 420mm (54/56), 440mm (58/61)
Stem	Ritchey 4-Axis, 3D forged 6061 alloy, 6" x 90mm (48/51), 100mm (54/56), 120mm (58/61)
Grips	Jamis suede tape
Seat Post	Ritchey Road, 27.2 x 350mm with alloy clamp
Saddle	Selle Royal Seta S1 with integrated clip system
Sizes	48, 51, 54, 56, 58, 61cm
Color	Charcoal
Weight	22.5 lbs



TECH FEATURES



UPGRADES/CHANGES FROM PREVIOUS MODEL

Same quality Jamis specification as previous model

REASONS TO UPGRADE FROM VENTURA SPORT

Jamis Ventura SSD designed disc brake frame and fork

Tektro Lyra mechanical disc brakes

Carbon composite ECO fork with flat mount disc brakes

Alex ATD 470 disc specific rims with TCS

Shimano Sora R3000 18-speed group

Selle Royal S1 Saddle

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
48	19.88 / 505	71°	75°	16.34 / 415	38.62 / 981	1.97 / 50	2.79 / 71	4.92 / 125	28.70 / 729	21.05 / 534.6	14.15 / 359.5
51	20.71 / 526	72°	74°	16.34 / 415	38.78 / 985	1.97 / 50	2.74 / 69.5	5.71 / 145	30.08 / 764	21.88 / 555.7	14.39 / 365.5
54	21.57 / 548	72.5°	73°	16.34 / 415	39.01 / 991	1.69 / 43	2.68 / 68	6.30 / 160	30.67 / 779	22.54 / 572.5	14.67 / 372.7
56	22.01 / 559	73°	73°	16.34 / 415	39.29 / 998	1.69 / 43	2.68 / 68	7.28 / 185	31.61 / 803	23.55 / 598.1	14.81 / 376.1
58	22.48 / 571	73°	73°	16.34 / 415	39.96 / 1015	1.69 / 43	2.62 / 66.5	8.07 / 205	32.32 / 821	24.24 / 615.8	15.07 / 382.7
61	22.91 / 582	73°	73°	16.34 / 415	40.39 / 1026	1.69 / 43	2.62 / 66.5	8.86 / 225	32.99 / 838	25.00 / 634.9	15.27 / 387.9