

# ALLEGRO COMP

## SPECIFICATIONS

Frame	Size Specific Design Triple-butted 6061 aluminum with redesigned rear triangle, flat mount disc brake mounts, internal cable routing, hydro-formed top and down tube, taper gauge "S" bend stays, replaceable derailleur hanger and fender/rack eyelets
Fork	Aluminum air-formed fork with disc brake mounts, aluminum steerer, low-rider carrier mounts, forged dropouts and fender eyelets
Headset	FSA Integrated IS threadless with nylon upper compression ring, 1 1/8"
Wheels	Alex TD26 double wall disc specific alloy rims, 32H, Formula 6-bolt alloy hubs with QR and 14g stainless steel spokes
Tires	Vittoria Randonneur with Double Shield puncture protection and reflective sidewalls, 700 x 32c
Derailleurs	Shimano Altus RD-M2000 rear and Shimano Altus FD-M370 front derailleur
Shiftlevers	Shimano Rapidfire Plus Altus SL-M2000, 27-speed
Chain	KMC Z9
Cassette	Shimano HG200 9-speed, 11-32T
Crankset	Shimano FC-M371, 48/36/26, 170mm (15-19"), 175mm (21-23")
BB Set	FSA sealed cartridge, 68 x 110.5mm
Pedals	Platform style, steel cage/resin body
Brakeset	Tektro HD-M275/276 hydraulic disc brakes with 160mm rotors and Tektro brake levers. 15-17" M276 (83mm reach); 19-23" M275 (88mm reach)
Handlebar	Jamis Flat bar, 6061 T-6 aluminum, 31.8 x 10" sweep x 580mm (15-17") 600mm (19-23")
Stem	Jamis Road 3D forged alloy, 10° rise x 90mm (15/17"), 105mm (19/21"), 115mm (23")
Grips	Anatomic double density kraton
Seat Post	Jamis alloy micro-adjust, 27.2 x 350mm alloy clamp with QR seatpin
Saddle	Jamis Touring with SL cover
Sizes	15", 17", 19", 21", 23"
Color	Nickel
Weight	25.75 lbs



Nickel

## UPGRADES/CHANGES FROM 2018

Redesigned SSD frame
Shimano 9-speed Altus group
Shimano 9-speed 11-32T cassette
Shimano FC-M371 48/36/26 crankset
Tektro HD-275/276 hydraulic disc brakes
Jamis Road 3D forged stem

## REASONS TO UPGRADE FROM ALLEGRO SPORT

Disc brake frame and fork
Aluminum air-formed fork
Shimano 9-speed Altus group
Shimano FC-M371 48/36/26 crankset
Tektro HD-275/276 hydraulic disc brakes

## ALLEGRO COMP GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
15	21.81 / 554	72°	73°	16.93 / 430	40.24 / 1022	1.89 / 48	2.26 / 57.5	4.72 / 120	28.82 / 732	21.50 / 546	15.20 / 386
17	22.28 / 566	72°	73°	16.93 / 430	40.90 / 1039	1.89 / 48	2.26 / 57.5	5.71 / 145	30.08 / 764	22.44 / 570	15.39 / 391
19	22.72 / 577	72°	73°	17.13 / 435	41.42 / 1052	1.89 / 48	2.16 / 55	6.93 / 170	31.50 / 800	23.27 / 591	15.59 / 396
21	23.19 / 589	73°	73°	17.32 / 440	41.69 / 1059	1.89 / 48	2.16 / 55	7.48 / 190	32.91 / 836	24.17 / 614	15.79 / 401
23	23.66 / 601	73°	73°	17.32 / 440	42.16 / 1071	1.89 / 48	2.16 / 55	8.46 / 215	34.17 / 868	25.12 / 638	25.40 / 406