

# COMMUTER 1

## SPECIFICATIONS

Frame	Hi-Tensile steel frame, new sloping design, kickstand mounts, forged dropouts and fender/rack eyelets
Fork	Jamis City/Cross hi-tensile steel unicrown, straight blades with low rider mounts and double fender eyelets
Headset	Water-resistant sealed mechanism, threaded, 1 1/8"
Wheels	Alex ID-19 double wall alloy rims with GSW sidewall, 32H, alloy hubs with QR and 14g stainless steel spokes
Tires	CST Corporal with puncture protection and silver safety stripe, 700 x 38c
Derailleurs	Shimano Altus, RD-M310 rear
Shiftlevers	Shimano RevoShift SL-RS35, 7-speed
Chain	KMC Z7
Cassette	Shimano MF-TZ500 7-speed, 14-34T
Crankset	Forged alloy crank, single 44T chainring, 170mm, with full length chainguard
BB Set	Sealed cartridge, 68 x 122.5mm
Pedals	Comfort platform with TPE non-slip insert
Brakeset	Forged alloy linear-pull brakes with Tektro CL530 ergonomic design alloy brake lever with kraton insert
Handlebar	Jamis ARC, 6061 aluminum, 25.4 x 35" sweep x 580mm (F 14", 18") 600mm (M 15", 17", 19", 21", 23")
Stem	Jamis alloy hi-rise, quill type, 35" x 90mm with 180mm quill
Grips	Anatomic double density kraton with reflective end plug
Seat Post	Jamis alloy micro-adjust, 25.4 x 350mm with alloy clamp and QR seatpinin
Saddle	Jamis Metro Sport with synthetic suede cover, burnished sides, gender specific
Accessories	Full coverage 45mm fenders with mud flaps, new designed Jamis carrier (capacity 18kg/40lbs.) with Jamis logo strap & rear reflector, micro bell and kickstand
Sizes	M: 15", 17", 19", 21", 23" S/O: 14", 18"
Color	M: Ink S/O: Sage
Weight	35 lbs



Ink

## UPGRADES/CHANGES FROM 2018

700x38 CST Corporal with puncture protection and silver safety stripe

## COMMUTER 1 GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
15"	22.32 / 567	70°	73.5°	17.52 / 445	42.28 / 1074	2.01 / 51	2.75 / 70	5.51 / 140	27.60 / 701	22.29 / 566.2	15.71 / 399
17"	22.91 / 582	70.5°	73.5°	17.52 / 445	42.72 / 1085	2.01 / 51	2.75 / 70	6.30 / 160	29.06 / 738	23.11 / 587	16.06 / 408
19"	23.27 / 591	71°	73.5°	17.52 / 445	42.87 / 1089	2.01 / 51	2.75 / 70	6.89 / 175	30.39 / 772	23.75 / 603.2	16.22 / 412
21"	23.82 / 605	71.5°	73°	17.52 / 445	42.99 / 1092	2.01 / 51	2.75 / 70	7.87 / 200	31.85 / 809	24.76 / 629	16.26 / 413
23"	24.21 / 615	71.5°	73°	17.52 / 445	43.43 / 1103	2.01 / 51	2.75 / 70	9.25 / 235	33.31 / 846	26.07 / 662.2	16.26 / 413
14"	22.09 / 561	70°	74.5°	17.52 / 445	42.44 / 1078	2.01 / 51	2.75 / 70	5.31 / 135	25.47 / 647	22.11 / 561.5	15.94 / 405
18"	22.48 / 571	71°	74°	17.52 / 445	42.24 / 1073	2.01 / 51	2.75 / 70	5.71 / 145	25.71 / 653	22.63 / 574.9	15.98 / 406



Sage