

DXT SPORT

SPECIFICATIONS

Frame	6061 aluminum formed top and down tube, 1 1/8" head tube, seat stays disc brake mounts, 34.9mm seat tube, replaceable derailleur hanger, fender/rack eyelets and ring lock mount eyelets
Fork	SR/Suntour SF15-NVX HLO, aluminum lowers, coil spring, 28mm stanchions, 1-1/8" steerer, aluminum crown, hydraulic lock out, 75mm travel
Headset	Internal Cup, threadless, 1 1/8"
Wheels	Alex TD26 disc specific double wall alloy rims, 36H, alloy disc hubs with QR and 14g stainless steel spokes
Tires	CST Dual Sport Tire, 700 x 42c
Derailleurs	Shimano Acera RD-M360 rear and Altus FD-M310 top swing front
Shiftlevers	Shimano Altus Rapid Fire SL-M310, 24-speed
Chain	KMC Z7
Cassette	Shimano HG31, 8-speed, 11-32T
Crankset	Shimano FC-TY301, 48/38/28T, 170mm (15-17"), 175mm (19-23")
BB Set	VP sealed cartridge, 68 x 122.5mm
Pedals	Platform style
Brakeset	Tektro HD-M275/276 hydraulic disc brakes with 160mm rotors and Tektro brake levers. 15" M276 (83mm reach); 17-23" M275 (88mm reach)
Handlebar	Jamis Riser bar, double-buttet aluminum, 25.4 x 10" sweep x 20mm rise x 640mm (15"), 660mm (17-23")
Stem	Jamis Trekking, 3D forged alloy, 15" rise, Length-60mm (15-17"), 90mm (19-23")
Grips	MTB Type Grip
Seat Post	Jamis alloy micro-adjust, 31.6 x 350mm alloy clamp with QR seatpin
Saddle	Jamis Touring with SL cover
Sizes	15", 17", 19", 21", 23"
Color	Ano Nickel
Weight	31.25 lbs



Ano Nickel

UPGRADES/CHANGES FROM 2018

Tektro HD-275/276 hydraulic disc brakes

Jamis double-buttet Alloy riser bar

CST Dual Sport Tire, 700 x 42c

REASONS TO UPGRADE FROM DXT

Shimano Acera/Altus 3x8 drivetrain

Tektro HD-275/276 hydraulic disc brakes

SR/Suntour NVX HLO suspension fork with hydraulic lockout

Jamis double-buttet Alloy riser bar

Cassette Freehub rear wheel

DXT SPORT GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
15	22.95 / 583	71°	73°	17.52 / 445	42.13 / 1070	1.57 / 40	2.36 / 60	4.33 / 110	29.45 / 748	24.41 / 620	15.55 / 395
17	23.54 / 598	71°	73°	17.52 / 445	42.72 / 1085	1.57 / 40	2.36 / 60	4.72 / 120	30.87 / 784	24.76 / 629	15.94 / 405
19	23.94 / 608	71°	73°	17.52 / 445	43.11 / 1095	1.57 / 40	2.36 / 60	5.31 / 135	31.93 / 811	25.35 / 644	16.18 / 411
21	24.53 / 623	71°	73°	17.52 / 445	43.74 / 1111	1.57 / 40	2.36 / 60	6.10 / 155	33.38 / 848	26.06 / 662	16.53 / 420
23	24.72 / 628	71°	73°	17.52 / 445	43.98 / 1117	1.57 / 40	2.36 / 60	6.89 / 175	34.76 / 883	26.81 / 681	16.50 / 419