

# PORTAL A2

## SPECIFICATIONS

Frame	Triple-butted 6061 aluminum, 130mm travel 3VO suspension, Enduro® Max sealed bearing pivots, 1.5 - 1 1/8" tapered head tube, 12x148mm thru-axle, Internal dropper post routing, Custom Jamis upper chainguide mounts, ISCG05 lower chainguide mounts, Rock Shox Deluxe R DebonAir shock, 10mm hardware, replaceable derailleur hanger
Fork	Rock Shox Revelation RC 29", 15x110mm axle, air spring compression, rebound adjust, tapered alloy steerer, 35mm stanchions, 130mm travel
Headset	FSA Orbit 1.5 Zero-Stack internal cup, 8mm cone spacer
Wheels	WTB ST i25 TCS 29" tubeless rims, 32H, Formula sealed bearing 15x110mm front & 12x148mm rear 6-bolt disc hubs, stainless spokes
Tires	Vittoria Martello 29 x 2.35", TNT tubeless
Derailleurs	Shimano SLX Shadow Plus, 11-speed
Shiftlevers	Shimano SLX, 1x11-speed
Chain	KMC X11, 11-speed
Cassette	Shimano M7000, 11-speed, 11-46T
Crankset	Race Face Ride, 32T
BB Set	Race Face BSA
Pedals	N/A
Brakeset	Shimano MT500 hydraulic disc, 180mm 6-bolt rotors
Handlebar	Race Face Ride, 760mm x 20mm rise, 35mm diameter
Stem	Race Face Ride, 50mm extension, 35mm clamp diameter
Grips	Jamis Lock-On
Seat Post	KS E10i Internal Dropper, Southpaw remote
Saddle	WTB Volt
Sizes	XS (14.5), S (15.5), M (17), L (19), XL (21)
Color	Charcoal
Weight	32.50 lbs



Charcoal

## TECH FEATURES



## UPGRADES/CHANGES FROM 2018

NEW MODEL!

## PORTAL GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
XS/14.5"	22.00 / 560	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	44.20 / 1122	LO 1.3 / 33 HI 1.0 / 26	3.70 / 95	LO 28.7 / 731 HI 29.1 / 738	23.50 / 597	15.60 / 397
S/15.5"	23.00 / 585	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	45.20 / 1148	LO 1.3 / 33 HI 1.0 / 26	4.10 / 105	LO 29.7 / 754 HI 29.9 / 761	23.90 / 606	16.50 / 418
M/17"	24.00 / 610	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	46.20 / 1173	LO 1.3 / 33 HI 1.0 / 26	4.50 / 115	LO 29.5 / 749 HI 29.8 / 756	24.20 / 615	17.30 / 439
L/19"	25.00 / 635	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	47.20 / 1198	LO 1.3 / 33 HI 1.0 / 26	4.90 / 125	LO 29.7 / 754 HI 29.9 / 761	24.60 / 625	18.20 / 461
XL/21"	26.00 / 660	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	48.20 / 1224	LO 1.3 / 33 HI 1.0 / 26	5.30 / 135	LO 30.5 / 774 HI 30.7 / 781	24.90 / 634	18.90 / 482