

# RENEGADE EXILE

## SPECIFICATIONS

Frame	Jamis Size Specific Design frame geometry, 6061 aluminum double-buttet SST main frame, top tube mounted full cable housing, 1.5 - 1 1/8" tapered head tube, 31.8mm seat tube for 27.2 seat post, seat stay disc brake mounts, replaceable derailleur hanger, 3 waterbottle mounts, rack and fender eyelets, clearance for 700x42c and 650x47c tires.
Fork	Jamis Adventure 6061 air-formed aluminum, tapered aluminum steerer, integrated cable cradles with post disc brake mounts, mounts for lowrider rack, waterbottle and fenders
Headset	FSA Orbit C-40B Internal/External, 1.5 - 1 1/8"
Wheels	WTB ST i23 TCS 2.0 (UST Tubeless Compliant System) disc rims, 32H, Formula alloy 6-bolt hubs and 14g stainless steel spokes
Tires	Donnelly X Plor MSO, 650 x 36c (44-48) 700 x 36c (51-61), 30TPI with protection belt
Derailleurs	Shimano Claris RD-R2000 GS rear and Claris FD-R2000 front with 31.8mm alloy clamp
Shiftlevers	Shimano Claris ST-R2000 Dual Control STI, 16-speed
Chain	KMC Z8
Cassette	Shimano HG41 8-speed, 11-34T
Crankset	FSA Vero, 50/34T, 165mm (44/48), 170mm (51) 172.5mm (54/56) 175mm (58/61)
BB Set	FSA sealed cartridge, 68 x 110.5mm
Pedals	N/A
Brakeset	Tektro Lyra mechanical cable actuated disc brake with 160mm wave rotors and Shimano Claris ST-R2000 levers
Handlebar	Ritchey Evomax Comp, 6061 aluminum, 73 reach, 120 drop with 12° flare, 31.8 x 400 (44) 420 (48-51) 440mm (54-56), 460mm (56-61)
Stem	Jamis Road 3D forged 6061 alloy, 7" x 70mm (44), 80mm (48/51), 90mm (54/56), 110mm (58/61)
Grips	Jamis suede tape with gel inserts
Seat Post	Jamis Road, micro-adjust, 27.2 x 350mm cromoly seat pin
Saddle	Selle Royal Asphalt with integrated clip system
Sizes	44 and 48x650, 51, 54, 56, 58, 61cm 700c
Color	Ano Palladium
Weight	25.25 lbs



Ano Palladium

## TECH FEATURES



## UPGRADES/CHANGES FROM 2018

WTB ST i23 TCS 2.0 Rim

Donnelly X Plor MSO, 36c with protection belt

Shimano 11-34T cassette

## RENEGADE EXPLORER/EXILE GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
44*	19.76 / 502	71°	73°	16.69 / 424	38.35 / 974	1.97 / 50	2.20 / 56	3.94 / 100	28.07 / 713	19.45 / 494	13.78 / 350
48*	20.39 / 518	71°	73°	16.69 / 424	39.01 / 991	1.97 / 50	2.14 / 54.5	4.92 / 125	28.78 / 731	20.35 / 517	14.13 / 359
51	20.98 / 533	71°	73°	16.81 / 427	39.53 / 1004	2.09 / 53	2.89 / 73.5	4.53 / 115	28.94 / 735	21.22 / 539	14.45 / 367
54	21.69 / 551	71.5°	73°	16.93 / 430	40.24 / 1022	2.09 / 53	2.83 / 72	5.71 / 145	30.51 / 775	22.36 / 568	14.80 / 376
56	22.40 / 569	71.5°	73°	16.93 / 430	40.98 / 1041	2.09 / 53	2.83 / 72	6.89 / 175	31.50 / 800	23.50 / 597	15.20 / 386
58	23.07 / 586	72°	73°	16.93 / 430	41.39 / 1051	1.97 / 50	2.77 / 70.5	7.87 / 200	32.44 / 824	24.49 / 622	15.55 / 395
61	23.66 / 601	72.5°	73°	17.20 / 435	41.98 / 1066	1.97 / 50	2.77 / 70.5	8.66 / 220	33.27 / 845	25.31 / 643	15.90 / 404

\*650b Wheel