

RENEGADE EXPLOIT

SPECIFICATIONS

Frame	Jamis Size Specific Design frame geometry, Reynolds 631 double-buttet chromoly main tubes, 44mm head tube for tapered fork, threaded BB shell, 12x142 Jamis MTS (Modular Thru-axle System), flat mount disc brake mounts, top tube mounted full cable housing, dropper post cable guides, 3 waterbottle mounts, rack and fender eyelets, clearance for 700x42c and 650x47c tires.
Fork	Jamis Adventure ECO monocoque carbon composite, 12mm Jamis MTS (Modular Thru-axle System) with stainless interface and carbon dropouts, tapered steerer with 1.5" hollow formed crown, flat mount disc brakes with internal cable routing, exposed fender, lowrider and water bottle eyelets
Headset	FSA Orbit ITA B Internal/External, 1.5 - 11/8"
Wheels	WTB ST Light i23 TCS 2.0 (UST Tubeless Compliant System) disc rims, 32H, Formula alloy Centerlock sealed bearing hubs with front 12mm/rear 12x142 thru-axle and 14g black stainless steel spokes
Tires	Donnelly X Plor MSO Tubeless, 650 x 36c (44-48) 700 x 36c (51-61), with protection belt and folding bead
Derailleurs	SRAM Apex 1 Long cage
Shiftlevers	SRAM Apex 1 HydroR levers, 11-speed
Chain	SRAM PC1110
Cassette	SRAM 1130 11-speed, 11-42T
Crankset	SRAM Apex, XSYNC 40T, 165mm (44/48), 170mm (51), 172.5mm (54/56), 175mm (58/61)
BB Set	SRAM GXP
Pedals	N/A
Brakeset	SRAM Apex 1 HydroR hydraulic disc brakes, Centerline 160mm rotors and SRAM Apex 1 HydroR 11-speed levers
Handlebar	Ritchey Evomax Comp, 6061 aluminum, 73 reach, 120 drop with 12° flare, 31.8 x 400 (44) 420 (48-51) 440mm (54-56), 460mm (56-61)
Stem	Ritchey 4-Axis 3D forged 6061 alloy, 6" x 70mm (44), 80mm (48/51), 90mm (54/56), 110mm (58/61)
Grips	Fizik Microtex Superlight Soft Touch with gel inserts
Seat Post	Jamis carbon fiber micro-adjust, 27.2 x 330mm with cromolloy seat pin
Saddle	Selle Royal Asphalt with integrated clip system
Sizes	44 and 48x650, 51, 54, 56, 58, 61cm 700c
Color	Flat Steel
Weight	23.5 lbs



Flat Steel

TECH FEATURES

REYNOLDS

SSD
SIZE SPECIFIC DESIGN

ECO

UPGRADES/CHANGES FROM 2018

SRAM Apex 1 group

SRAM Apex 1 hydraulic disc brakes with Centerline 160mm rotors

SRAM Apex 1 crankset with XSYNC 40T

WTB ST Light i23 TCS 2.0 Rim

Donnelly X Plor MSO Tubeless, 36c with protection belt and Kevlar folding bead

SRAM 11-42T cassette

Selle Royal Asphalt Saddle with integrated clip system

REASONS TO UPGRADE FROM RENEGADE EXPAT

Renegade Adventure Reynolds 631 double-buttet chromoly frame

SRAM Apex 1 group

SRAM Apex 1 hydraulic disc brakes with Centerline 160mm rotors

SRAM Apex 1 crankset with XSYNC 40T

WTB ST Light i23 TCS 2.0 Rim

Donnelly X Plor MSO Tubeless, 36c with protection belt and Kevlar folding bead

Formula sealed bearing Centerlock hubs

RENEGADE ESCAPE/EXPLOIT GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
44*	19.76 / 502	71°	73°	16.69 / 424	38.38 / 975	1.97 / 50	2.20 / 56	3.86 / 98	28.15 / 715	19.49 / 495	13.82 / 351
48*	20.35 / 517	71°	73°	16.69 / 424	39.05 / 992	1.97 / 50	2.14 / 54.5	4.72 / 120	28.82 / 732	20.27 / 515	14.17 / 360
51	20.98 / 533	71°	73°	16.81 / 427	39.57 / 1005	2.09 / 53	2.89 / 73.5	3.94 / 100	29.88 / 759	20.98 / 535	14.53 / 369
54	21.69 / 551	71.5°	73°	16.93 / 430	40.27 / 1023	2.09 / 53	2.83 / 72	5.20 / 132	31.10 / 790	22.24 / 565	14.88 / 378
56	22.44 / 570	71.5°	73°	16.93 / 430	41.02 / 1042	2.09 / 53	2.83 / 72	6.42 / 163	31.93 / 811	23.42 / 595	15.24 / 387
58	23.07 / 586	72°	73°	16.93 / 430	41.38 / 1051	1.97 / 50	2.77 / 70.5	7.40 / 188	32.87 / 835	24.41 / 620	15.59 / 396
61	23.66 / 601	72.5°	73°	17.20 / 435	41.97 / 1066	1.97 / 50	2.77 / 70.5	8.15 / 207	33.70 / 856	25.20 / 640	15.94 / 405

*650b Wheel