

# SEQUEL

## SPECIFICATIONS

Frame	Jamis Size Specific Design frame geometry, Reynolds 520 double-butted chromoly main tubes, threaded BB shell, chain stay disc brake mounts, 3 waterbottle mounts, rack and fender eyelets
Fork	Jamis Chromoly fork, 12mm dropouts, 45mm crown, IS mount disc brakes, fender, lowrider and water bottle eyelets
Headset	FSA IS3 Internal headset 1 1/8"
Wheels	WTB ST i23 TCS 2.0 (UST Tubeless Compliant System) disc rims, 32H, Formula alloy 6-bolt sealed bearing hubs with front 12mm/rear 12x142 thru-axle and 14g black stainless steel spokes
Tires	WTB Byway Tire with DNA compound, 650 x 47c
Derailleurs	Shimano Deore RD-M6000 GS Shadow Plus rear
Shiftlevers	Shimano Deore RapidFire Plus SL-M6000, 10-speed
Chain	KMC X10
Cassette	Shimano CS-HG500, 10-speed, 11-42T
Crankset	FSA Vero Pro crank, 40T, 15/17" 165 19/21" 170. 23" 175mm
BB Set	FSA sealed cartridge, 68 x 110.5mm
Pedals	Platform style, alloy
Brakeset	Shimano BR-MT200 hydraulic disc brakes with 160mm stainless 6-bolt rotors and Shimano BL-MT200 levers
Handlebar	Jamis Riser bar, aluminum, 10° sweep, 3° up sweep, 20mm rise, 31.8 x 680mm (15/17/19") 700mm (21/23")
Stem	Jamis, 3D forged alloy, 3° rise, Length-40mm (15/17"), 50mm (19/21"), 60mm (23")
Grips	MTB Kraton Grip
Seat Post	Jamis alloy micro-adjust, 27.2 x 350mm alloy clamp with QR seatpin
Saddle	Selle Royal Asphalt with integrated clip system
Sizes	15", 17", 19", 21", 23"
Color	Charcoal or Desert Storm
Weight	28.0 lbs



Charcoal

## SEQUEL GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
15"	21.02 / 534	71°	74.5°	17.13 / 435	40.59 / 1031	2.09 / 53	2.76 / 70	3.54 / 90	27.80 / 706	20.91 / 531	15.24 / 387
17"	21.65 / 550	71°	74.5°	17.32 / 440	41.50 / 1054	2.09 / 53	2.76 / 70	4.72 / 120	29.13 / 740	22.01 / 559	15.55 / 395
19"	22.95 / 583	71.5°	73°	17.52 / 445	42.17 / 1071	1.97 / 50	2.56 / 65	5.91 / 150	30.59 / 777	23.07 / 586	15.91 / 404
21"	23.62 / 600	71.5°	73°	17.72 / 450	43.07 / 1094	1.97 / 50	2.36 / 60	7.09 / 180	31.97 / 812	24.17 / 614	16.22 / 412
23"	24.21 / 615	71.5°	73°	17.72 / 450	42.78 / 1112	1.97 / 50	2.36 / 60	4.73 / 210	33.43 / 849	25.12 / 638	16.54 / 420