

# CODA S1 FEMME

## SPECIFICATIONS

Frame	Size Specific Design Disc Brake Reynolds 520 double-butted chromoly main tubes, extended head tube with reinforced collars, double tapered cromoly stays, forged dropouts and fender/rack eyelets
Fork	Jamis full carbon composite with carbon steerer, disc brake post mounts, low-rider carrier mounts and carbon drop out with stainless steel tabs and fender eyelets
Headset	Threadless, 1 1/8"
Wheels	Alex TD-26 double wall disc specific alloy rims, 32H, Joytec hubs with QR and 14g stainless steel spokes
Tires	Vittoria Randonneur with anti-puncture protection and reflective sidewalls, 700 x 32c
Derailleurs	Shimano Acera RD-M360 SGS rear and Altus FD-M310 top swing front
Shiftlevers	Shimano RapidFire Plus SL-M315, 24-speed
Chain	KMC Z8
Cassette	Shimano HG41 8-speed, 11-34T
Crankset	SR/Suntour XCC, 48/38/28T, 170mm (14-18")
BB Set	FSA sealed cartridge, 68 x 110.5mm
Pedals	Full alloy platform, toe clip attachable
Brakeset	Tektro HD-276 hydraulic disc brakes with 83mm reach, 160mm rotors and Tektro brake levers.
Handlebar	Jamis Flat bar, 6061 T-6 aluminum, 25.4 x 10" sweep x 580mm
Stem	Jamis Road 3D forged alloy, 25.4 x 17" x 90mm (14-18")
Grips	Anatomic double density kraton
Seat Post	Jamis alloy micro-adjust, 27.2 x 350mm alloy clamp with QR seatpin
Saddle	Selle Royal Asphalt GF with integrated clip system
Sizes	14", 16", 18"
Color	Slate
Weight	26.25 lbs



Slate

## UPGRADES/CHANGES FROM 2019

Shimano RapidFire Plus SL-M315 shifters  
Joytec alloy hubs

## REASONS TO UPGRADE FROM CODA S2

Reynolds 520 double-butted chromoly main tube disc brake frame  
Jamis full carbon fork  
Selle Royal Asphalt Saddle with integrated clip system  
Tektro HD-275/276 hydraulic disc brakes  
Alex TD-26 double walled disc specific alloy rims  
Vittoria Randonneur with anti-puncture protection and reflective sidewalls, 700 x 32c

## CODA S1 FEMME GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
14	22.05 / 560	71°	73°	16.93 / 430	40.94 / 1040	1.97 / 50	2.26 / 57.5	4.09 / 104	27.75 / 705	20.98 / 533	15.63 / 397
16	22.52 / 572	71°	73°	16.93 / 430	41.42 / 1052	1.97 / 50	2.26 / 57.5	4.65 / 118	28.74 / 730	21.50 / 546	15.94 / 405
18	22.95 / 583	71°	73°	17.13 / 435	42.09 / 1069	1.97 / 50	2.26 / 57.5	5.00 / 127	29.80 / 757	22.01 / 559	16.22 / 412