

CODA S2 FEMME

SPECIFICATIONS

Frame	Size Specific Design Double-butted chromoly main tubes, extended head tube with reinforced collars, double tapered cromoly stays, forged dropouts and fender/rack eyelets
Fork	Hi-Ten tapered straight blade unicrown with bulge butted steerer, low-rider carry mounts and forged dropouts with 2 fender eyelets
Headset	Threadless, 1 1/8"
Wheels	Alex ID-19 double wall alloy rims with GSW sidewall, 32H, Formula alloy hubs with QR and 14g stainless steel spokes
Tires	Kenda Kwick Tendril with anti-puncture protection and reflective sidewalls, 700 x 32c
Derailleurs	Shimano Acera M360 SGS rear and FD-TY710 bottom pull front
Shiftlevers	Shimano RapidFire Plus SL-M315, 24-speed
Chain	KMC Z8
Cassette	Shimano HG41 8-speed, 11-32T
Crankset	SR/Suntour XCC, 48/38/28T, 170mm (14-18")
BB Set	Sealed cartridge, 68 x 110.5mm
Pedals	Platform style, steel cage/resin body
Brakeset	Tektro alloy linear-pull brakes with front power modulator and Tektro brake levers
Handlebar	Jamis Flat bar, 6061 T-6 aluminum, 25.4 x 10" sweep x 580mm
Stem	Jamis Road, 3D forged 6061 alloy, 25.4 x 17" x 75mm (14-18")
Grips	Anatomic double density kraton
Seat Post	Jamis alloy micro-adjust, 27.2 x 350mm alloy clamp with QR seatpin
Saddle	Jamis Touring Femme with SL top
Sizes	14", 16", 18"
Color	Radiant Teal or Gloss Black
Weight	26.75 lbs



Gloss Black



Radiant Teal

UPGRADES/CHANGES FROM 2019

Shimano RapidFire Plus SL-M315 shifters

Joytec alloy hubs

REASONS TO UPGRADE FROM CODA S3

Alex ID-19 rims with GSW sidewall

Shimano Acera M360 rear and RD-TY710 front detailleuers

Shimano RapidFire Plus SL-M315 shifters/tektro brake lever

Shimano 8-speed 11-32T cassette

CODA S2 FEMME GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
14	22.05 / 560	71°	73°	16.93 / 430	40.94 / 1040	1.97 / 50	2.26 / 57.5	4.09 / 104	27.75 / 705	20.98 / 533	14.61 / 371
16	22.52 / 572	71°	73°	16.93 / 430	41.42 / 1052	1.97 / 50	2.26 / 57.5	4.65 / 118	28.74 / 730	21.50 / 546	14.72 / 374
18	22.95 / 583	71°	73°	17.13 / 435	42.09 / 1069	1.97 / 50	2.26 / 57.5	5.16 / 131	29.80 / 757	22.01 / 559	14.88 / 378