

PORTAL A1

SPECIFICATIONS

Frame	Triple-buttet 6061 aluminum, 130mm travel 3VO suspension, Enduro® Max sealed bearing pivots, 1.5 - 1 1/8" tapered head tube, 12x148mm thru-axle, Internal dropper post routing, Custom Jamis upper chainguide mounts, ISCG05 lower chainguide mounts, Fox Float DPS Performance Series EVOL shock w/3-position compression, 10mm hardware, replaceable derailleur hanger
Fork	Fox Rhythm 34 Float 29" w/ sweep adjust compression & lock-out, 15x110mm axle, air spring compression, rebound adjust, tapered alloy steerer, 130mm travel
Headset	FSA Orbit IS Integrated, 8mm cone spacer
Wheels	DT Swiss M1900 SPLINE 25 29" tubeless wheels, DT 370 hubs, DT Champion spokes
Tires	Vittoria Martello 29 x 2.35", TNT tubeless
Derailleurs	Shimano XT, 12-speed
Shiftlevers	Shimano XT, 1x12-speed
Chain	KMC X12, 12-speed
Cassette	Shimano XT M8100, 12-speed, 10-51T
Crankset	Race Face Aeffect, 32T
BB Set	Race Face BSA
Pedals	N/A
Brakeset	Shimano XT M8100 Ice-Tech hydraulic disc, RT-800 180mm front & 160mm rear centerlock rotors
Handlebar	Race Face Aeffect R, 780mm x 20mm rise, 35mm diameter
Stem	Race Face Aeffect R, 50mm extension, 35mm clamp diameter
Grips	Jamis Lock-On
Seat Post	KS Rage Dropper, Southpaw remote
Saddle	WTB Volt
Sizes	XS (14.5), S (15.5), M (17), L (19), XL (21)
Color	Raw Aluminum
Weight	31.5 lbs



Available as frameset

Raw Aluminum

TECH FEATURES



UPGRADES/CHANGES FROM 2019

- Shimano XT 12-speed drivetrain
- DT Swiss M1900 SPLINE 25 wheelset
- Shimano XT brakes
- KS Rage Dropper post

REASONS TO UPGRADE FROM PORTAL A2

- Fox suspension
- Shimano XT drivetrain & brakes
- DT Swiss M1900 SPLINE 25 wheelset

PORTAL GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
S/15.5"	23.00 / 585	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	45.20 / 1148	LO 1.3 / 33 HI 1.0 / 26	4.10 / 105	LO 29.7 / 754 HI 29.9 / 761	23.90 / 606	16.50 / 418
M/17"	24.00 / 610	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	46.20 / 1173	LO 1.3 / 33 HI 1.0 / 26	4.50 / 115	LO 29.5 / 749 HI 29.8 / 756	24.20 / 615	17.30 / 439
L/19"	25.00 / 635	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	47.20 / 1198	LO 1.3 / 33 HI 1.0 / 26	4.90 / 125	LO 29.7 / 754 HI 29.9 / 761	24.60 / 625	18.20 / 461
XL/21"	26.00 / 660	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	48.20 / 1224	LO 1.3 / 33 HI 1.0 / 26	5.30 / 135	LO 30.5 / 774 HI 30.7 / 781	24.90 / 634	18.90 / 482