

# PORTAL C1

## SPECIFICATIONS

Frame	Dyad Pro High Modulus Carbon Fiber, 130mm travel 3VO suspension, Enduro® Max sealed bearing pivots, 1.5 - 11/8" tapered head tube, 12x148mm thru-axle, Internal dropper post routing, Custom Jamis upper chainguide, MRP SXg lower chainguide, Fox DHX2 Factory Series coil shock w/2-position compression switch, SLS 450lb Spring, high/low speed compression, high/low speed rebound, 10mm hardware, replaceable derailleur hanger
Fork	Fox Factory 36 Float 29" w/ 3-position adjust compression & lock-out, 15x110mm axle, air spring compression, rebound adjust, tapered alloy steerer, 140mm travel
Headset	FSA Orbit IS Integrated, 8mm cone spacer
Wheels	Stans Arch CB7 Carbon 29" tubeless wheels, 15x110mm axle front and 12x148mm rear NEO hubs, Sapim Race spokes
Tires	Vittoria Martello 29 x 2.35", TNT tubeless
Derailleurs	SRAM XX1 Eagle, 12-speed
Shiftlevers	SRAM XX1 Eagle, 1x12-speed
Chain	SRAM XX1 Eagle, 12-speed
Cassette	SRAM XG1299, 12-speed, 10-50T
Crankset	Truvativ Descendant Carbon, 32T
BB Set	SRAM DUB
Pedals	N/A
Brakeset	TRP G-Spec Trail SL 4-piston hydraulic disc, TR-33 180mm front & rear 6-bolt rotors
Handlebar	Race Face Turbine R, 780mm x 20mm rise, 35mm diameter
Stem	Race Face Turbine R, 50mm extension, 35mm clamp diameter
Grips	Jamis Lock-On
Seat Post	Fox Transfer Dropper, 1x remote
Saddle	WTB Volt
Sizes	S (15.5), M (17), L (19), XL (21)
Color	Desert Storm
Weight	30.75 lbs



Desert Storm



Available as frameset

## TECH FEATURES



## UPGRADES/CHANGES FROM 2019

New for 2020!

## REASONS TO UPGRADE FROM PORTAL C2

- Fox DHX2 Coil Shock
- Fox 36 fork
- SRAM XX1 Eagle drivetrain
- Stans Arch Carbon wheelset
- TRP G-spec Trail brakeset

## PORTAL GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
S/15.5"	23.00 / 585	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	45.20 / 1148	LO 1.3 / 33 HI 1.0 / 26	4.10 / 105	LO 29.7 / 754 HI 29.9 / 761	23.90 / 606	16.50 / 418
M/17"	24.00 / 610	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	46.20 / 1173	LO 1.3 / 33 HI 1.0 / 26	4.50 / 115	LO 29.5 / 749 HI 29.8 / 756	24.20 / 615	17.30 / 439
L/19"	25.00 / 635	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	47.20 / 1198	LO 1.3 / 33 HI 1.0 / 26	4.90 / 125	LO 29.7 / 754 HI 29.9 / 761	24.60 / 625	18.20 / 461
XL/21"	26.00 / 660	LO 67.5° HI 68°	LO 74.5° HI 75°	17.20 / 437	48.20 / 1224	LO 1.3 / 33 HI 1.0 / 26	5.30 / 135	LO 30.5 / 774 HI 30.7 / 781	24.90 / 634	18.90 / 482