

# RENEGADE S2

## SPECIFICATIONS

Frame	UPDATED Jamis Size Specific Design frame geometry, Reynolds 631 double-butted chromoly main tubes, tapered head tube for tapered fork, oval seat stays, Di2 compatible threaded BB shell, 12x142 Jamis MTS (Modular Thru-axle System), flat mount disc brake mounts, top tube mounted full cable housing, dropper post cable guides, 3 waterbottle mounts, TT mounts, rack and fender eyelets.
Fork	Jamis Adventure ECO monocoque carbon composite, 12mm Jamis MTS (Modular Thru-axle System) with stainless interface and carbon dropouts, tapered steerer with 1.5" hollow formed crown, flat mount disc brakes with internal cable routing, exposed fender, lowrider and water bottle eyelets
Headset	FSA IS2 sealed bearing Internal with 15.3mm top cone, 1.5 - 1 1/8"
Wheels	WTB ST Light i23 TCS 2.0 (UST Tubeless Compliant System) disc rims, 32H, Formula alloy 6-bolt sealed bearing hubs, 14g black stainless steel spokes and front 12mm/rear 12x142 thru-axle with Switch Lever
Tires	Donnelly X Plor MSO, 650 x 36c (44-48) 700 x 40c (51-61), with protection belt and folding bead
Derailleurs	Shimano GRX RD-RX812 Shadow Plus
Shiftlevers	Shimano GRX ST-RX600 Dual Control STI, 22-speed.
Chain	KMC x11 EPT Anti-Rust
Cassette	Shimano 11-speed, 11-42T
Crankset	Shimano GRX FC-RX600, 40T, 170mm (44/48/51), 172.5mm (54/56), 175mm (58/61)
BB Set	Shimano
Pedals	N/A
Brakeset	Shimano GRX BR-RX400 flat mount hydraulic disc brakes with resin pads, Shimano 160mm rotors with GRX ST-RX600 Dual Control STI levers
Handlebar	Ritchey Baquiano Comp, 6061 aluminum, 73 reach, 118 ergonomic drop with 12° flare, 31.8 x 400 (44) 420 (48-51) 440mm (54-56), 460mm (56-61)
Stem	Ritchey 4-Axis 3D forged 6061 alloy, 6" x 60mm (44), 70mm (48/51), 80mm (54/56), 100mm (58/61)
Grips	Velo EVA gel with gel inserts
Seat Post	Jamis carbon fiber micro-adjust, 27.2 x 330mm with cromo seat pin
Saddle	Selle Royal Asphalt with integrated clip system
Sizes	44 and 48x650, 51, 54, 56, 58, 61cm 700c
Color	Dark Ash
Weight	23.5 lbs



Dark Ash

## TECH FEATURES

**REYNOLDS**



**ECO**

## UPGRADES/CHANGES FROM 2019

Updated Renegade Adventure Reynolds 631 double-butted frame

Shimano GRX ST-RX600 Dual Control STI, 22-speed

Shimano GRX BR-RX400 hydraulic disc brakes

Shimano GRX RX-R812 Shadow Plus rear derailleur

Shimano GRX FC-RX600 40T crankset with 11-42T cassette

Donnelly X Plor MSO Tubeless 700 x 40c (51-61)

Ritchey Baquiano Comp bar with ergonomic drop

## REASONS TO UPGRADE FROM RENEGADE S3

Updated Renegade Adventure Reynolds 631 double-butted frame

Shimano GRX ST-RX600 Dual Control STI, 22-speed

Shimano GRX BR-RX400 hydraulic disc brakes

Shimano GRX RX-R812 Shadow Plus rear derailleur

Shimano GRX FC-RX600 40T crankset with 11-42T cassette

WTB ST Light i23 TCS 2.0 Rim

Donnelly X Plor MSO Tubeless, 650 x 36c (44-48) 700 x 40c (51-61)

Joytec sealed bearing hubs

## RENEGADE S1/2 GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
44 650	19.76 / 502	71°	73°	16.69 / 424	38.58 / 980	1.97 / 50	2.14 / 54.5	4.76 / 121	28.15 / 715	19.88 / 505	13.82 / 351
48 650	20.51 / 521	71°	73°	16.69 / 424	39.17 / 995	1.97 / 50	2.14 / 54.5	5.59 / 142	28.82 / 732	20.67 / 525	14.17 / 360
51	21.10 / 536	71°	73°	16.81 / 427	39.69 / 1008	2.09 / 53	2.89 / 73.5	4.88 / 124	29.88 / 759	21.46 / 545	14.53 / 369
54	21.81 / 554	71.5°	73°	16.93 / 430	40.39 / 1026	2.09 / 53	2.83 / 72	6.10 / 155	31.10 / 790	22.64 / 575	14.88 / 378
56	22.52 / 572	71.5°	73°	16.93 / 430	41.14 / 1045	2.09 / 53	2.83 / 72	7.36 / 187	31.93 / 811	23.82 / 605	15.24 / 387
58	23.19 / 589	72°	73°	16.93 / 430	41.54 / 1055	1.97 / 50	2.77 / 70.5	8.31 / 211	32.87 / 835	24.80 / 630	15.59 / 396
61	23.78 / 604	72.5°	73°	17.2 / 435	41.89 / 1064	1.97 / 50	2.77 / 70.5	9.06 / 230	33.70 / 856	25.59 / 650	15.94 / 405