

PORTAL C4

SPECIFICATIONS

Frame	Dyad Pro High Modulus Carbon Fiber, 130mm travel 3VO suspension, Enduro® Max sealed bearing pivots, 1.5 - 1 1/8" tapered head tube, 12x148mm thru-axle, Internal dropper post routing, Custom Jamis upper chainguide mounts, ISCG05 lower chainguide mounts, Fox Float DPS Performance Series EVOL shock w/3-position compression, 10mm shock hardware, replaceable derailleur hanger
Fork	Fox 34 Rhythm Series Float 29" w/ sweep adjust compression & lock-out, 15x110mm axle, air spring compression, rebound adjust, tapered alloy steerer, 130mm travel
Headset	FSA Orbit IS Integrated, 8mm cone spacer
Wheels	Stan's No Tubes Flow D 29" rims, Shimano MT410 15x110mm front & 12x148mm rear hubs, stainless spokes
Tires	Vittoria Mazza 29 x 2.4", TNT tubeless
Derailleurs	Shimano Deore, 12-speed
Shiftlevers	Shimano Deore, 1x12-speed
Chain	KMC X12, 12-speed
Cassette	Shimano M6100, 12-speed, 10-51T
Crankset	Race Face Ride, 32T
BB Set	Race Face BSA
Pedals	N/A
Brakeset	Shimano MT420 4-piston hydraulic disc, 180mm front & 160mm rear RT30 rotors
Handlebar	Race Face Ride, 760mm x 20mm rise, 35mm diameter
Stem	Race Face Ride, 50mm extension, 35mm clamp diameter
Grips	Jamis Lock-On
Seat Post	KS Rage Dropper, Southpaw remote
Saddle	WTB Volt
Sizes	S (15.5), M (17), L (19), XL (21)
Color	Riptide
Weight	31.25 lbs



Riptide

MTB - 3VO SUSPENSION

TECH FEATURES



UPGRADES/CHANGES FROM 2020

New for 2021!

REASONS TO UPGRADE FROM PORTAL A2

Dyad Pro High Modulus Carbon Fiber Frame

PORTAL GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
S/15.5"	23.0 / 585	LO 67.5° HI 68°	LO 74.5° HI 75°	17.2 / 437	45 / 1148	LO 1.3 / 33 HI 1.0 / 26	4.1 / 105	LO 29.7 / 754 HI 29.9 / 761	23.9 / 606	16.5 / 418
M/17"	24.0 / 610	LO 67.5° HI 68°	LO 74.5° HI 75°	17.2 / 437	46 / 1173	LO 1.3 / 33 HI 1.0 / 26	4.5 / 115	LO 29.5 / 749 HI 29.8 / 756	24.2 / 615	17.3 / 439
L/19"	25.0 / 635	LO 67.5° HI 68°	LO 74.5° HI 75°	17.2 / 437	47 / 1198	LO 1.3 / 33 HI 1.0 / 26	4.9 / 125	LO 29.7 / 754 HI 29.9 / 761	24.6 / 625	18.2 / 461
XL/21"	26.0 / 660	LO 67.5° HI 68°	LO 74.5° HI 75°	17.2 / 437	48 / 1224	LO 1.3 / 33 HI 1.0 / 26	5.3 / 135	LO 30.5 / 774 HI 30.7 / 781	24.9 / 634	18.9 / 482