

RENEGADE S2

SPECIFICATIONS

Frame	UPDATED Jamis Size Specific Design frame geometry, Reynolds 631 double-butted chromoly main tubes, tapered head tube for tapered fork, oval seat stays, Di2 compatible, threaded T47 BB shell, 12x142 Jamis MTS (Modular Thru-axle System), flat mount disc brake mounts, down tube mounted full cable housing, internal dropper post ready, 3 waterbottle mounts, TT mounts, rack and fender eyelets.
Fork	UPDATED Jamis Adventure ECO monocoque carbon composite, 12mm Jamis MTS (Modular Thru-axle System) with stainless interface and carbon dropouts, tapered steerer with 1.5" hollow formed crown, flat mount disc brakes with internal cable routing, exposed fender, lowrider and 3 water bottle eyelets
Headset	FSA IS2 sealed bearing Internal with 15.3mm top cone, 1.5 - 1 1/8"
Wheels	STANS CREST S1 Tubeless disc rims, i23, 32H, Bear Paws alloy 6-bolt sealed bearing hubs, 14g black stainless steel spokes with front 12mm/rear 12x142 thru-axle with Switch Lever
Tires	WTB Raddler 700Cx40C, Distance+ Compound, Supple Tubeless Casing, TCS Aramid Bead (48-61) WTB VENTURE 650Bx40C, Black Sidewall, Dual DNA Compound, Lightweight Tubeless Casing, TCS Aramid Bead (44)
Derailleurs	Shimano GRX RD-RX812 Shadow Plus
Shiftlevers	Shimano GRX ST-RX600 Dual Control STI, 11-speed.
Chain	KMC x11 EPT Anti-Rust
Cassette	Shimano 11-speed, 11-42T
Crankset	Shimano GRX FC-RX600, 40T, 170mm (44/48/51), 172.5mm (54/56), 175mm (58/61)
BB Set	FSA T47
Pedals	N/A
Brakeset	Shimano GRX BR-RX400 flat mount hydraulic disc brakes with resin pads, Shimano 160mm rotors with GRX ST-RX600 Dual Control STI levers
Handlebar	Ritchey Baquiano Comp, 6061 aluminum, 73 reach, 118 ergonomic drop with 12° flare, 31.8 x 400 (44) 420 (48-51) 440mm (54-56), 460mm (56-61)
Stem	Ritchey 4-Axis 3D forged 6061 alloy, 6" x 60mm (44), 70mm (48/51), 80mm (54-56), 100mm (58/61)
Grips	Velo EVA gel with gel inserts
Seat Post	Jamis carbon fiber micro-adjust, 27.2 x 330mm with chromo seat pin
Saddle	Selle Royal Asphalt with integrated clip system
Sizes	44cm x 650 and 48, 51, 54, 56, 58, 61cm 700c
Color	Storm Grey
Weight	23.5 lbs



Storm Grey

ROAD - GRAVEL / ADVENTURE

TECH FEATURES



UPGRADES/CHANGES FROM 2020

Updated Renegade Adventure Reynolds 631 double-butted chromoly frame

Updated Renegade Adventure ECO carbon fork

STANS CREST S1 Tubeless disc i23 rims with Bear Paws alloy 6-bolt sealed bearing hubs

WTB Raddler 700Cx40C, Distance+ Compound

REASONS TO UPGRADE FROM RENEGADE S3

Updated Renegade Adventure Reynolds 631 double-butted chromoly frame

Shimano GRX ST-RX600 Dual Control STI, 22-speed

Shimano GRX RX-R812 Shadow Plus rear derailleur

Shimano GRX FC-RX600 40T crankset

STANS CREST S1 Tubeless disc i23 rims with Bear Paws alloy sealed bearing hubs and WTB Raddler 700Cx40C tires

RENEGADE S1/2 GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
44 650	19.76 / 502	71°	73°	16.69 / 424	38.58 / 980	1.97 / 50	2.14 / 54.5	4.76 / 121	28.15 / 715	19.88 / 505	13.82 / 351
48	20.51 / 521	71°	73°	16.69 / 424	39.17 / 995	1.97 / 50	2.14 / 54.5	5.59 / 142	28.82 / 732	20.67 / 525	14.17 / 360
51	21.10 / 536	71°	73°	16.81 / 427	39.69 / 1008	2.09 / 53	2.89 / 73.5	4.88 / 124	29.88 / 759	21.46 / 545	14.53 / 369
54	21.81 / 554	71.5°	73°	16.93 / 430	40.39 / 1026	2.09 / 53	2.83 / 72	6.10 / 155	31.10 / 790	22.64 / 575	14.88 / 378
56	22.52 / 572	71.5°	73°	16.93 / 430	41.14 / 1045	2.09 / 53	2.83 / 72	7.36 / 187	31.93 / 811	23.82 / 605	15.24 / 387
58	23.19 / 589	72°	73°	16.93 / 430	41.54 / 1055	1.97 / 50	2.77 / 70.5	8.31 / 211	32.87 / 835	24.80 / 630	15.59 / 396
61	23.78 / 604	72.5°	73°	17.20 / 435	41.89 / 1064	1.97 / 50	2.77 / 70.5	9.06 / 230	33.70 / 856	25.59 / 650	15.94 / 405