

RENEGADE EXILE

SPECIFICATIONS

Frame	Jamis SSD frame geometry, 6061 aluminum double-buttet SST main frame, top tube mounted full cable housing, 1.5 - 1 1/8" tapered head tube, 31.8mm seat tube for 27.2 seat post, seat stay disc brake mounts, replaceable derailleur hanger, 3 waterbottle mounts, rack and fender eyelets, clearance for 40c tires.
Fork	Jamis Adventure 6061 aluminum, tapered chromoly steerer, integrated cable cradles with post disc brake mounts and fender eyelets
Headset	FSA Orbit C-40B Internal/External, 1.5 - 1 1/8"
Wheels	WTB i23 STP disc rims with TCS (UST Tubeless Compliant System), 32H, Formula alloy 6-bolt hubs and 14g stainless steel spokes
Tires	Clement X Plor MSO 700 x 36c, 30TPI with protection belt
Derailleurs	Shimano Claris RD-2400 rear and Claris FD-2400 front with 28.6mm alloy clamp
Shiftlevers	Shimano Claris ST-2400 Dual Control STI, 16-speed
Chain	KMC Z7
Cassette	Shimano HG41 8-speed, 11-32T
Crankset	FSA Vero, 50/34T, 165mm (48), 170mm (51) 172.5mm (54/56) 175mm (58/61)
BB Set	FSA sealed cartridge, 68 x 110.5mm
Pedals	N/A
Brakeset	Tektro Lyra mechanical cable actuated disc brake with 160mm wave rotors and Shimano Claris ST-2400 levers
Handlebar	Ritchey Evomax Comp, 6061 aluminum, 73 reach, 120 drop with 12° flare, 31.8 x 420 (48-51) 440mm (54-56), 460mm (56-61)
Stem	Jamis Road 3D forged 6061 alloy, 7" x 80mm (48/51), 90mm (54/56), 110mm (58/61)
Grips	Jamis suede tape
Seat Post	Jamis Road, micro-adjust, 27.2 x 350mm chromo seat pin
Saddle	Jamis Road with SL top, front and rear bumpers and satin steel rails
Sizes	48, 51, 54, 56, 58, 61cm
Color	Ano Black
Weight	24.0 lbs



Cosmic Dust

TECH FEATURES



UPGRADES/CHANGES FROM PREVIOUS MODEL

WTB i23 STP disc rim with TCS (UST Tubeless Compliant System)

Clement X Plor MSO 700 x 36c, 30TPI with protection belt

Shimano HG41 8-speed 11-32T

FSA Vero compact double, 50/34T

GEOMETRY

SIZE	TT EFFECTIVE	HT ANGLE	ST ANGLE	CHAINSTAY	WHEELBASE	FORK RAKE	BB DROP	HEADTUBE	STANDOVER	STACK	REACH
48	20.43 / 519	70.5°	73°	16.81 / 427	39.25 / 997	2.24 / 57	2.89 / 73.5	3.74 / 95	28.54 / 725	20.27 / 515	14.17 / 360
51	21.02 / 534	71°	73°	16.81 / 427	39.57 / 1005	2.09 / 53	2.89 / 73.5	4.53 / 115	28.94 / 735	21.06 / 535	14.53 / 369
54	21.69 / 551	71.5°	73°	16.93 / 430	40.27 / 1023	2.09 / 53	2.83 / 72	5.71 / 145	30.51 / 775	22.24 / 565	14.88 / 378
56	22.44 / 570	71.5°	73°	16.93 / 430	41.02 / 1042	2.09 / 53	2.83 / 72	6.89 / 175	31.50 / 800	23.43 / 595	15.24 / 387
58	23.07 / 586	72°	73°	16.93 / 430	41.38 / 1051	1.97 / 50	2.77 / 70.5	7.87 / 200	32.44 / 824	24.41 / 620	15.59 / 396
61	23.66 / 601	72.5°	73°	17.2 / 435	41.97 / 1066	1.97 / 50	2.77 / 70.5	8.66 / 220	33.27 / 845	25.20 / 640	15.94 / 405